

Safe Work. Strong Business.



Surat Gas Project Updated CSG WMMP Annual Report

Reporting Period: 22 October 2022 to 21 October 2023

Version	1.0
Released	20 January 2024
Document Owner	Groundwater Manager
Document Author	Team Lead Hydrogeology
Document Status	Issued for Use

Please see document administration section for more information





Safe Work. Strong Business.

Contents

1.	Purpose	5
2.	Surat Gas Project Status	5
2.1	Well Installations	6
2.2	Well Production	6
3.	Monitoring and Management Programs	11
3.1	Groundwater pressure/level	11
3.2	Groundwater quality	19
3.3	Ground movement monitoring	31
3.4	Update to monitoring network	43
4.	Updated Impact Predictions	53
4.1	Groundwater drawdown extent	53
5.	WMMP Revision	59
5.1	Field assessment of potential TGDEs	60
5.2	Potential terrestrial groundwater dependent ecosystems	61
6.	Compliance with the WMMP	63
7.	Document Administration	65
8.	References	67
Appendix	A – Groundwater Level Monitoring Bores Hydrographs	68
Appendix	B – Groundwater quality results	153
Appendix	C – Mann-Kendall Summary	157
Appendix	D – Field assessment of potential TGDEs related to the SGP WM	MP
using the	2019 UWIR	159
Appendix	E – Ground Movement Investigation Summary	160



List Tables

Table 1: SGP Production well details and start dates	6
Table 2: 2022 – 2023 water production volumes by month and annual total	9
Table 3: 2021 UWIR groundwater chemistry monitoring points	19
Table 4: Summary field water quality percentiles for Springbok Sandstone	20
Table 5: Summary of changes to the Updated CSG WMMP monitoring points to align wit	h
the 2021 UWIR monitoring requirements	44
Table 6: Revised Updated CSG WMMP Monitoring Network as per the 2021 UWIR WMS	3.48
Table 7: 2021 UWIR groundwater sampling parameters and frequency for groundwater	
monitoring points	53

List of Figures

Figure 2-1: SGP production wells' locations that have commenced production during this	
reporting period (22 October 2022 – 21 October 2023)	10
Figure 3-1: Condamine Alluvium monitoring bores hydrograph	13
Figure 3-2: Central Condamine Alluvium area monitoring bores hydrograph	13
Figure 3-3: Springbok Sandstone monitoring bores hydrograph	14
Figure 3-4: Hutton Sandstone monitoring bores hydrograph	15
Figure 3-5: Precipice Sandstone monitoring bores hydrograph	16
Figure 3-6: Juandah Coal Measures monitoring bores hydrograph – southern area	17
Figure 3-7: Juandah Coal Measures monitoring bores hydrograph – central area	17
Figure 3-8: Juandah Coal Measures monitoring bores hydrograph – northern area	18
Figure 3-9: Taroom Coal Measures monitoring bores hydrograph	18
Figure 3-10:3-10: Springbok Sandstone electrical conductivity	22
Figure 3-11: Springbok Sandstone pHFigure 3-11: Springbok Sandstone pH	22
Figure 3-12: Springbok Sandstone: Calcium	24
Figure 3-13: Springbok Sandstone: Chloride	24
Figure 3-14: Springbok Sandstone: Magnesium	24
Figure 3-15: Springbok Sandstone: Sodium	24
Figure 3-16: Springbok Sandstone: Sulphate	25
Figure 3-17: Springbok Sandstone TDS	25
Figure 3-18: Condamine Alluvium Piper Diagram	26
Figure 3-19: Westbourne Formation Piper Diagram	27
Figure 3-20: Springbok Sandstone Piper Diagram	28
Figure 3-21: WCM Piper Diagram	29
Figure 3-22: Hutton Sandstone Piper Diagram	29
Figure 3-23: Precipice Sandstone Piper Diagram	30
Figure 3-24: Summary of Mann-Kendall trend analysis for Springbok Sandstone monitoring	J
bore Plainview 36	31
Figure 3-25: 2021 UWIR predicted long-term CSG-induced subsidence across the Surat	
Basin (after OGIA, 2021)	33
Figure 3-26: Predicted maximum change in ground slope from CSG-induced subsidence	
within the Condamine Alluvium area (after OGIA, 2021)	34
Figure 3-27: Probabilities of predicted subsidence and resulting change in slope within the	
Condamine Alluvium area (after OGIA, 2021)	35



Figure 3-28: InSAR Median Ground Movement (July 2022 to June 2023 inclusive)	38
Figure 3-29: 1x1km Grid Cell ID 2039 showing location of transects under	39
Figure 3-30: Profile of Transect 3 on Grid Cell ID 2039	40
Figure 3-31: 1x1km Grid Cell ID 2571 showing location of transects undertaken	41
Figure 3-32: Profile of Transect 1 on Grid Cell ID 2571	41
Figure 3-33: 1x1km Grid Cell ID 2346 showing location of transects undertaken	42
Figure 3-34: Profile of Transect 5 on Grid Cell ID 2346	42
Figure 3-35: 2021 UWIR Arrow Monitoring Network – southern tenure	51
Figure 3-36: 2021 UWIR Arrow Monitoring Network – northern tenure	52
Figure 4-1: Updated CSG WMMP and 2019 UWIR Combined Springbok Sandstone Ion	g-
term affected area	55
Figure 4-2: Updated CSG WMMP and 2019 UWIR Combined WCM long-term affected a	area
	56
Figure 4-3: Updated CSG WMMP and 2019 UWIR Combined Hutton Sandstone long-te	erm
affected area	57
Figure 4-4: Updated CSG WMMP and 2019 UWIR Combined Precipice Sandstone long	-
term affected area	58



1. Purpose

Arrow Energy's (Arrow) Surat Gas Project (SGP) was approved by the Australian Government under the *Environment Protection and Biodiversity Conservation Act 1999* (EPBC Act) decision 2010/5344 on 19 December 2013. The conditions attached to approval EPBC 2010/5344 require a Stage 1 Coal Seam Gas (CSG) Water Monitoring and Management Plan (WMMP) (as required under condition 13, and approved by the Australian Government on 18 December 2018) and an Updated CSG WMMP (as required under condition 17, and approved by the Australian Government on 22 November 2019) be prepared.

Section 8.2.4 of the SGP Updated WMMP requires Arrow to publish an annual report presenting a summary of progress towards Arrow's commitments and document Arrow's compliance against the approval conditions. This annual report is required to be prepared within three months of the anniversary date of the SGP commencement, which was 22 October 2020. This Report has been prepared to fulfil these obligations for the reporting period of 22 October 2022 to 21 October 2023 and provides:

- a summary of relevant monitoring results and analysis and interpretation of data, including:
 - groundwater levels (Section 3.1)
 - o groundwater chemistry results (Section 3.2)
 - subsidence monitoring results (Section 3.3)
- documentation of corrective actions implemented to address exceedances of trigger thresholds, limits, or non-compliance with approval conditions (Sections 3 and 6)
- details of any updates to the Field Development Plan (FDP) and implications for water monitoring and management (Section 4)
- reporting of any relevant ongoing studies and research projects, and includes any supporting technical studies as appendices to the annual report (Section 5)
- documentation of Arrow's compliance against the approval conditions over the preceding 12 months, including monitoring obligations and implementation of the early warning monitoring system (EWMS) (Section 6)
- reporting against the performance measure criteria detailed in Section 8.3 of the SGP Updated WMMP (Sections 3, 5 and 6).

2. Surat Gas Project Status

The SGP commenced on 22 October 2020 and, in the first 12 months, production had not started from any SGP production wells during that reporting period and, as such, no water was produced from these wells during that reporting period.



During this reporting period (22 October 2022 – 21 October 2023), 138 SGP production wells have started production, whereas during the previous reporting period (22 October 2021 – 21 October 2022), 37 SGP wells had commenced production.

2.1 Well Installations

A total of 247 production wells have been installed since commencement of the SGP.

2.2 Well Production

Table 1 presents the location and start date of the SGP production wells, which commenced production during this reporting period. Figure 2-1 shows the location of these wells. The monthly water production volumes for all SGP wells are summarised in Table 2.

Well Name	Easting (m)	Northing (m)	PL	Production Start date
Longswamp 171	316525	6980771	PL260	14-Oct-23
Longswamp 172	316540	6980769	PL260	14-Oct-23
Longswamp 173	316555	6980767	PL260	14-Oct-23
Longswamp 174	316570	6980765	PL260	14-Oct-23
Longswamp 241	315156	6981638	PL260	14-Oct-23
Longswamp 242	315154	6981623	PL260	14-Oct-23
Longswamp 243	315152	6981608	PL260	14-Oct-23
Longswamp 244	315150	6981594	PL260	14-Oct-23
Longswamp 245	314844	6980026	PL260	14-Oct-23
Longswamp 246	314842	6980012	PL260	14-Oct-23
Longswamp 247	314840	6979997	PL260	14-Oct-23
Longswamp 248	314838	6979982	PL260	14-Oct-23
Longswamp 249	316003	6979900	PL260	14-Oct-23
Longswamp 261	315993	6977710	PL260	14-Oct-23
Longswamp 262	315990	6977725	PL260	14-Oct-23
Longswamp 263	315988	6977740	PL260	14-Oct-23
Longswamp 264	315985	6977755	PL260	14-Oct-23
Longswamp 271	317414	6979177	PL260	14-Oct-23
Longswamp 272	317412	6979162	PL260	14-Oct-23
Longswamp 273	317410	6979147	PL260	14-Oct-23
Longswamp 274	317408	6979132	PL260	14-Oct-23
Longswamp 275	317406	6979117	PL260	14-Oct-23
Longswamp 278	318082	6978197	PL260	14-Oct-23
Longswamp 279	318067	6978197	PL260	14-Oct-23
Longswamp 281	317825	6981297	PL260	14-Oct-23
Longswamp 282	317823	6981282	PL260	14-Oct-23
Longswamp 283	317821	6981267	PL260	14-Oct-23
Tipton 401	319363	6981637	PL198	14-Oct-23

Table 1: SGP Production well details and start dates





Tipton 402	319364	6981652	PL198	14-Oct-23
Tipton 411	319234	6980558	PL198	14-Oct-23
Tipton 412	319236	6980573	PL198	14-Oct-23
Tipton 413	319238	6980587	PL198	14-Oct-23
Tipton 421	321026	6981329	PL198	14-Oct-23
Tipton 422	321024	6981314	PL198	14-Oct-23
Tipton 423	321023	6981299	PL198	14-Oct-23
Tipton 441	318417	6977162	PL198	14-Oct-23
Tipton 442	318432	6977161	PL198	14-Oct-23
Tipton 443	318447	6977159	PL198	14-Oct-23
Longswamp 276	317432	6978276	PL260	11-Oct-23
Tipton 314	317579	6968802	PL198	3-Oct-23
Plainview 101	322133	6978345	PL238	29-Sep-23
Plainview 102	322118	6978345	PL238	29-Sep-23
Plainview 103	322103	6978344	PL238	29-Sep-23
Plainview 104	322088	6978344	PL238	29-Sep-23
Tipton 451	320428	6977280	PL198	28-Sep-23
Tipton 452	320413	6977278	PL198	28-Sep-23
Tipton 453	320398	6977277	PL198	28-Sep-23
Tipton 454	320383	6977275	PL198	28-Sep-23
Tipton 461	320238	6979083	PL198	17-Sep-23
Tipton 462	320239	6979068	PL198	17-Sep-23
Tipton 463	320239	6979053	PL198	17-Sep-23
Tipton 464	320240	6979038	PL198	17-Sep-23
Longswamp 221	314530	6974090	PL260	15-Jul-23
Longswamp 222	314518	6974099	PL260	15-Jul-23
Longswamp 223	314506	6974108	PL260	15-Jul-23
Longswamp 224	314494	6974117	PL260	15-Jul-23
Longswamp 225	314482	6974126	PL260	15-Jul-23
Longswamp 267	316562	6974394	PL260	2-Jun-23
Longswamp 115	312369	6975944	PL260	14-May-23
Longswamp 111	312429	6975945	PL260	12-May-23
Longswamp 112	312414	6975944	PL260	12-May-23
Longswamp 113	312399	6975944	PL260	12-May-23
Longswamp 114	312384	6975944	PL260	12-May-23
Longswamp 116	312354	6975943	PL260	12-May-23
Longswamp 236	314899	6976003	PL260	12-May-23
Longswamp 117	312339	6975943	PL260	11-May-23
Longswamp 231	314974	6976006	PL260	11-May-23
Longswamp 232	314959	6976005	PL260	11-May-23
Longswamp 233	314944	6976005	PL260	11-May-23
Longswamp 234	314929	6976004	PL260	11-May-23
Longswamp 235	314914	6976004	PL260	11-May-23
Longswamp 237	314884	6976003	PL260	11-May-23



Longswamp 238	314869	6976002	PL260	11-May-23
Longswamp 251	310890	6976557	PL260	11-May-23
Longswamp 252	310875	6976559	PL260	11-May-23
Longswamp 266	316259	6975610	PL260	11-May-23
Tipton 391	318191	6974909	PL198	11-May-23
Tipton 392	318176	6974911	PL198	11-May-23
Tipton 393	318161	6974913	PL198	11-May-23
Tipton 394	318146	6974915	PL198	11-May-23
Tipton 395	318131	6974916	PL198	11-May-23
Tipton 396	318116	6974918	PL198	11-May-23
Tipton 397	318101	6974920	PL198	11-May-23
Tipton 398	318087	6974922	PL198	11-May-23
Tipton 445	317067	6976581	PL198	11-May-23
Tipton 446	317069	6976595	PL198	11-May-23
Longswamp 131	314579	6978311	PL260	15-Apr-23
Longswamp 132	314577	6978326	PL260	12-Apr-23
Longswamp 133	314575	6978341	PL260	12-Apr-23
Longswamp 134	314572	6978356	PL260	6-Apr-23
Longswamp 135	314570	6978370	PL260	4-Apr-23
Longswamp 136	314568	6978385	PL260	4-Apr-23
Longswamp 124	312150	6978755	PL260	26-Mar-23
Longswamp 121	312144	6978710	PL260	25-Mar-23
Longswamp 122	312146	6978725	PL260	25-Mar-23
Longswamp 123	312148	6978740	PL260	25-Mar-23
Longswamp 125	312152	6978770	PL260	25-Mar-23
Longswamp 126	312154	6978785	PL260	25-Mar-23
Longswamp 127	312156	6978800	PL260	25-Mar-23
Longswamp 128	312157	6978814	PL260	25-Mar-23
Longswamp 145	311547	6981111	PL260	21-Mar-23
Longswamp 147	311576	6981107	PL260	21-Mar-23
Longswamp 144	311532	6981113	PL260	20-Mar-23
Longswamp 146	311561	6981109	PL260	20-Mar-23
Longswamp 148	311591	6981105	PL260	20-Mar-23
Longswamp 141	311487	6981119	PL260	18-Mar-23
Longswamp 142	311502	6981117	PL260	18-Mar-23
Longswamp 143	311517	6981115	PL260	18-Mar-23
Stratheden 92	305001	6990782	PL 252	7-Mar-23
Kogan North 282	291803	7008595	PL194	6-Mar-23
Kogan North 283	290799	7008998	PL194	6-Mar-23
Kogan North 284	290160	7008714	PL194	6-Mar-23
Kogan North 285	289974	7009456	PL194	6-Mar-23
Kogan North 287	291657	7009535	PL194	6-Mar-23
Longswamp 155	311255	6985022	PL260	21-Feb-23
Longswamp 156	311253	6985007	PL260	21-Feb-23






Longswamp 157	311251	6984992	PL260	21-Feb-23
Longswamp 158	311250	6984978	PL260	21-Feb-23
Stratheden 211	309500	6985234	PL 252	18-Feb-23
Stratheden 212	309498	6985219	PL 252	18-Feb-23
Stratheden 213	309496	6985204	PL 252	18-Feb-23
Stratheden 214	309494	6985189	PL 252	18-Feb-23
Longswamp 351	311394	6987399	PL260	30-Jan-23
Longswamp 341	310767	6989183	PL260	24-Jan-23
Longswamp 342	310769	6989198	PL260	24-Jan-23
Longswamp 352	311392	6987384	PL260	24-Jan-23
Longswamp 353	311390	6987369	PL260	24-Jan-23
Longswamp 354	311388	6987354	PL260	24-Jan-23
Stratheden 231	309391	6986891	PL 252	24-Jan-23
Stratheden 232	309376	6986893	PL 252	24-Jan-23
Stratheden 233	309361	6986894	PL 252	24-Jan-23
Stratheden 234	309346	6986896	PL 252	24-Jan-23
Longswamp 343	310770	6989212	PL260	20-Jan-23
Longswamp 344	310772	6989227	PL260	20-Jan-23
Longswamp 151	311339	6983161	PL260	17-Jan-23
Longswamp 152	311325	6983162	PL260	17-Jan-23
Longswamp 153	311310	6983164	PL260	17-Jan-23
Longswamp 154	311295	6983166	PL260	17-Jan-23

Table 2: 2022 – 2023 water production volumes by month and annual total

Month	Volume extracted (ML)
November 2022	140.8
December 2022	126.7
January 2023	132.5
February 2023	193.5
March 2023	246.8
April 2023	281.5
May 2023	394.8
June 2023	430.2
July 2023	426.8
August 2023	308.2
September 2023	393.1
October 2023	524.9
Total annual	3599.8





ARROW ENERGY - SURAT GAS PROJECT

Figure 2-1: SGP production wells' locations that have commenced production during this reporting period (22 October 2022 – 21 October 2023)



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 10 of 168

3. Monitoring and Management Programs

3.1 Groundwater pressure/level

Data collection

Groundwater pressure and level data were collected from all operational WMMP monitoring points throughout the reporting period except for Burunga Lane-174 and Burunga Lane-176 which was unable to be accessed due to ongoing land access negotiations (Refer to Table 5). In accordance with Section 7.3 of the SGP Updated WMMP, the locations monitored, and the frequency of monitoring were carried out throughout the reporting period in alignment with the most current Underground Water Impact Report (UWIR), which was the 2021 UWIR prepared by the Office of Groundwater Impact Assessment (OGIA, 2021). A summary of the groundwater pressure / level monitoring program as required by the 2021 UWIR is provided in Section 3.4.

Throughout the reporting period there were instances where hourly data were unable to be collected due to monitoring equipment failure or access to the monitoring point was not in place. These monitoring points are listed below:

- Plainview 16 telemetry issue, intermittent from December 2022 to February 2023
- Tipton-197 Skid offline from April 2023 onwards
- Carn Brea-18/19/20 (single skid) offline up to May 2023
- Plainview 34 skid offline from May to July 2023
- CastIdean-18 skid offline from May to August 2023
- Daandine-164 intermittent from June 2023
- Tipton 196A skid offline from July 2023
- Tipton 200 possible hardware calibration issue from July 2023
- Tipton-194 skid offline from August 2023
- Kedron-570 skid offline from September 2023

It should be noted that although not all hourly data were collected from the monitoring points noted here, the majority of hourly data for the reporting period was collected from almost all of these monitoring points. Individual hydrographs for each monitoring point are provided in Appendix A.

In accordance with Section 9.12 of the 2021 UWIR (OGIA, 2021), Arrow provided to OGIA a WMS network implementation report and WMS water monitoring report by the required dates of 1 April and 1 October 2023.



Data analysis

An analysis of data collected to the end of the reporting period is provided in the following sections, noting that water production from SGP production wells continued during the reporting period and, as a result, changes in observed groundwater levels/pressure have been analysed with respect to groundwater extraction.

EWMS comparison

Biannual comparison of the collected groundwater level/pressure data against the EWMS values was undertaken within 90 days of the end of each six-monthly monitoring period. No EWMS exceedances were identified during the reporting period and illustrations of these comparisons are provided in Appendix A.

Condamine Alluvium trend analysis

A hydrograph of the groundwater level data collected from the Condamine Alluvium monitoring bores is shown in Figure 3-1. The data show general groundwater flow in the Condamine Alluvium, within the vicinity of Arrow's monitoring network, is from south to north.

Groundwater level trends are variable within the Condamine Alluvium. The majority of the bores located in the central Condamine Alluvium area (groundwater elevation between 305 and 330 m AHD) displaying strong seasonal responses to non-CSG groundwater take (Figure 3-2) and thus the greatest observed drawdown (and generally subsequent recovery).

A long-term groundwater level data (Figure 3-1) depict a seasonal change in groundwater level trend across most monitoring bores. Bores 42230209, Macalister 5, Pampas 18, Plainview 37, Tipton 195, Tipton 203, Tipton 221, and Wyalla-16 have a generally stable trend with no observable seasonal variation. Carn Brea 23, Carn Brea 17, Daandine-161, Macalister 7, Plainview 25, 42231463, and 42231370 also have a relatively stable trend but show seasonal responses.

Groundwater level of the bore Stratheden-62 was previously following seasonal variations, but it has a more stable trend over the last 4 years. The SGP production wells located near Stratheden-62 commenced extraction from the reservoir in April 2022 and the water level in this bore has remained stable throughout the reporting period.

Bore Tipton 204 groundwater levels have previously shown declining trends but in the last three years have started to show an increasing trend. Groundwater level of Mt Haystack 5 shows a declining trend during this reporting period. It should be noted that this bore has previously also shown a declining trend between 2016 – 2019 before commencement of the SGP and an increasing trend during 2019 – 2022.






Figure 3-1: Condamine Alluvium monitoring bores hydrograph




Figure 3-2: Central Condamine Alluvium area monitoring bores hydrograph



Springbok Sandstone trend analysis

Groundwater levels/pressure in the Springbok Sandstone monitoring bores displayed varying trends; however, all monitoring points except for Glenburnie 20 (given its monitoring interval is a perched seepage zone and is not representative of the regional water table) and part of the monitoring record for Hopeland-17 (still recovering from groundwater sampling) displayed a groundwater elevation between 290 and 350 m AHD during this reporting period (Figure 3-3).

Bores Stratheden-63, Meenawarra-21, Glenburnie-18 (following a period of pressure equalisation succeeding bore installation), Glenburnie 20, Plainview 36, Longswamp 29, Longswamp 33 and Tipton 202 displayed generally stable groundwater pressure trends. Hopeland-17 displayed variability in its groundwater pressure, most likely a result of nearby CSG production on neighbouring non-Arrow tenements (as noted in Section 5.6.2.2 of the 2021 UWIR (OGIA, 2021)), a workover in May 2020 to install a new pressure gauge (the gauge failed in November 2018) and swabbing of the bore in December 2020 to collect a groundwater sample (which the bore was still recovering from at the end of the reporting period as a result of low permeability of the formation). The SGP production wells located near Stratheden-63 commenced extraction from April 2022, a response to this production is not evident in the water level data during this time. These trends in the Springbok Sandstone monitoring bores continued throughout the reporting year.




Figure 3-3: Springbok Sandstone monitoring bores hydrograph

Hutton Sandstone trend analysis

All Hutton Sandstone monitoring bores showed a long-term declining trend (Figure 3-4) at rates that are consistent with Section 5.6.2.1 of the 2021 UWIR (OGIA, 2021), which is up to 2 m per year. The largest observed drawdown (21.1 m) has been recorded in bore Wyalla-17 since 2019, the majority of which



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 14 of 168

occurred within the first six months of installation, with a drawdown rate of less than 2 m/year since then. Newly installed monitoring point at Daandine-123 (July 2020) recorded a drawdown of 14.2 m since August 2020 (rate of 4.3 m/year). The least drawdown of 0.07 m (rate of 0.01 m/year) has been observed in Tipton-153 since 2019. The small observed drawdown rate in Kedron-570 (0.18 m/year) is also consistent with the 2021 UWIR (OGIA, 2021) which states that there is generally no groundwater level trends in the Hutton Sandstone north of the Great Dividing Range. The initial steeper drawdown curves observed in Wyalla-17 and when a new pressure gauge was installed in Daandine-123 (July 2020), are likely a result of pressure equalisation between the bore and the formation following workover of the bores to install the gauges. The monitoring bore Plainview 16 was installed relatively recently and has correspondingly short periods of monitoring. However, the Hutton Sandstone groundwater level is stable at this bore. Similar to Plainview, Tipton 200 was installed recently but as mentioned previously there was some hardware calibration issue. In spite of this, the Hutton Sandstone groundwater level at this bore was subjected to a minor fluctuation between 311.0 - 323.5 mAHD. These long-term trends have continued throughout the reporting period, noting that data have not been collected from Burunga Lane-176 since 2018 due to ongoing land access negotiations (Table 5).




Figure 3-4: Hutton Sandstone monitoring bores hydrograph

Precipice Sandstone trend analysis

Observed groundwater pressure trends in the Precipice Sandstone monitoring bores shows a declining trend in the monitoring bores located further south within Arrow's tenure (Figure 3-5). These trends are consistent with that described in Section 5.6.2.4 of the 2021 UWIR (OGIA, 2021) where there is extensive non-CSG development (in parallel with the Moonie oil field) which has resulted in regionally observed declines in groundwater pressure in the south. The 2021 UWIR indicates in areas where reinjection is occurring correlates to



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 15 of 168

increasing groundwater level trends, however, no groundwater level data was collected from Arrows northern bore (Burunga Lane-174 – land access is not in place) during this annual period to confirm whether this trend was occurring in this area. The lowest rate of drawdown (0.47 m/year) and highest rate of drawdown (1.31 m/year) during this reporting period have been recorded in Wyalla-17 and Carn Brea-20, respectively.




Figure 3-5: Precipice Sandstone monitoring bores hydrograph

Walloon Coal Measures trend analysis

Hydrographs for the Walloon Coal Measures (WCM) observed groundwater pressures are presented in Figure 3-6 to Figure 3-9. The WCM are the reservoir target for production of CSG. The pressure data have been split into four hydrographs since there are a large number of monitoring points and variations in observed pressure value. The hydrographs demonstrate, as predicted, the pressure responses at those locations close to CSG operations such as those monitoring points located at Daandine production field, Tipton production field and Hopeland area, while those monitoring bores further away from CSG operations display a more subdued (or no) pressure response. This relationship between observed drawdown in the WCM and distance from nearest production is consistent with that reported for the WCM across the Surat CMA in the 2019 and 2021 UWIR (OGIA 2019, 2021).

Production from SGP production wells started in April 2022. Further declines in groundwater levels at Longswamp-7 sites were observed after this date as SGP production wells are closer to this bore than other productions wells, however these monitoring points were already showing a decline in groundwater levels due to these other production wells. Insignificant changes in groundwater levels at Daandine-134 and Daandine-254 sites were observed during this reporting period, where CSG production is approaching maturity.



The groundwater levels at Longswamp 34 during this reporting period were consistent with previous years decreasing trend.




Figure 3-6: Juandah Coal Measures monitoring bores hydrograph - southern area




Figure 3-7: Juandah Coal Measures monitoring bores hydrograph - central area



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 17 of 168




Figure 3-8: Juandah Coal Measures monitoring bores hydrograph - northern area




Figure 3-9: Taroom Coal Measures monitoring bores hydrograph



3.2 Groundwater quality

Data collection

Groundwater samples were collected from all operational WMMP monitoring points throughout the reporting period where land access arrangements were in place. In accordance with Section 7.3 of the SGP Updated WMMP, the locations monitored and frequency of monitoring throughout the reporting period were in alignment with the current UWIR, which was the 2021 version. A summary of changes to the groundwater quality monitoring program is provided in Section 3.4 and a list of monitoring bores sampled during the reporting period is provided in Table 3. It should be noted that the 2021 UWIR specifies (Table 9-4) that sampling is no longer required from monitoring points where five samples have been collected (including one sample of dissolved strontium and strontium isotopes (⁸⁷Sr/⁸⁶Sr) in Springbok Sandstone, Hutton Sandstone and Precipice Sandstone monitoring points).

A summary of groundwater sampling conducted during the reporting period is provided in Table 3. These groundwater samples were analysed for the 2021 UWIR suite which is provided in Table 7 and the results are provided in Appendix B.

Bore Name	OGIA MP ID	Formation	SAMPLING COMPLETED DURING REPORTING PERIOD [*]
Burunga Lane-176	477	Hutton Sandstone	No sampling completed due to no land access
Carn Brea-17	39	Condamine Alluvium	Not required
Carn Brea-18	41	WCM	Not required
Carn Brea-19	45	Hutton Sandstone	Not required
Daandine-121	183	Hutton Sandstone	Not required
RN 42230209	282	Condamine Alluvium	Not required
Glenburnie-18	739	Hutton Sandstone	Not required
Plainview 36	790	Springbok Sandstone	Sampled November 2022 and April 2023
Stratheden-63	623	Springbok Sandstone	Not required
Tipton-195	85	Condamine Alluvium	Not required
Tipton-197	89	WCM	Not required
Tipton 202	830	Springbok Sandstone	Sampled November 2022, April 2023 and October 2023
Wyalla-16	248	Condamine Alluvium	Not required
RN 42231370	52	Condamine Alluvium	Not required

Table 3: 2021 UWIR groundwater chemistry monitoring points

* Refer to Table 5 and Table 6 for sampling requirements (2021 UWIR monitoring requirement).

Data analysis

The 2021 UWIR discusses the water quality parameters for each groundwater monitoring zone in terms of the 20th 50th, and 80th percentiles. The section below discusses in detail the water quality results for sole formation where water quality



data was obtained during this annual reporting period (Springbok Sandstone) as well as a brief comparison of the hydrogeochemistry of the other formations in the form of piper diagrams to demonstrate the differences in proportions of major ions in groundwater samples.

Field parameters

Springbok Sandstone

A statistical summary of the historical field water quality parameters is provided in Table 4 for Springbok Sandstone considering 20th, 50th and 80th percentiles. These statistics were compared to those in the Environmental Protection (Water and Wetland Biodiversity) Policy 2019 (EPP), specifically the Lower GAB, Eastern Springbok Outcrop values. The purpose of the EPP is to achieve the objective of the Environmental Protection Act 1994 in relation to Queensland waters— that is, to protect Queensland's water environment whilst allowing for development that is ecologically sustainable. This is achieved through adopting or deriving local Water Quality Objectives (WQO). In deciding local water quality objectives for Queensland waters, Section 8 of the EPP (Water and Wetland Biodiversity) gives precedence to site specific studies for a water (i.e., local studies) (DES 2023).

The 3 bores monitoring this unit have 80th percentiles for EC below the 80th percentile EPP WQ objective. However, Stratheden-63 and Tipton 202 have higher 20th and 50th percentiles than the EPP objectives. The pH measured at the 3 bores is higher than the EPP objectives for the 20th, 50th and 80th percentile. It should be noted that the pH measured at Tipton 202 has likely been affected by cement grout ingress to the gravel pack within the wellbore. Therefore, the pH values measured at Tipton 202 were not included in the calculation of pH percentiles for all bores.

Parameter		Plainview 36	Stratheden -63	Tipton 202	All bores	EPP WQ objective
EC (µS/cm)	Count	6	9	3	18	
	20 per*	1299.00	3865.80	4559.2 0	1366.40	1420.00
	50 per	1326.00	4121.00	5257.0 0	3986.50	3175.00
	80 per	1406.00	4461.00	6848.8 0	4581.00	9480.00
рН	Count	6	9	3	18	
	20 per	8.16	8.92	11.99	8.22	7.50
	50 per	8.20	9.30	12.13	8.64	8.00
	80 per	8.32	9.79	12.56	9.54	8.40
REDOX (mV)	Count	6	9	3	18	
	20 per	-118.50	-237.54	-137.02	-216.78	NA
	50 per	-64.75	-212.40	-129.40	-142.35	NA



	80 per	43.30	-181.64	-36.22	-2.02	NA
TEMP (°C)	Count	6	9	3	18	
	20 per	22.20	22.18	22.46	22.14	NA
	50 per	24.25	26.20	23.00	24.55	NA
	80 per	28.00	30.50	23.72	29.02	NA

per = percentile

Tipton 202 elevated pH values

Tipton 202 was drilled to monitor groundwater level and quality in the Springbok Sandstone. The lithological log records the bore intersected Condamine Alluvium to 22.9 mbgl, before continuing to TD of 137m in the underlying Springbok Sandstone.

Elevated pH ranging from 11.89 to 12.85 has been recorded only in 3 samples from Tipton 202 collected to date. Hydroxide Alkalinity as $CaCO_3$ has also been reported from Tipton 202. High pH values and the presence of Hydroxide Alkalinity are both indicators of cement grout influencing the groundwater hydrochemistry within the borehole. It is likely that cement grout has breached the bentonite seal and percolated into the gravel pack within the annulus. Bore construction details indicate there is approximately 95 m of grout vertically separating the base of the alluvium from the top of the bentonite seal. Groundwater salinity, as EC in samples from this bore, ranges from 4,094 to 7,900 μ S/cm.

The Queensland Department of Regional Development, Manufacturing and Water (RDMW) has a monitoring bore RN 42231280 drilled and completed in the Condamine alluvium, located approximately 2,600 m to the east of Tipton 202. A total of 12 groundwater samples have been collected and analysed from this bore, with the reported salinity as EC ranging from 655 to 976 μ S/cm. As the groundwater salinity measured in Springbok Sandstone at Tipton 202 is much higher (EC 4,094 to 7,900 μ S/cm) than the salinity in the Condamine Alluvium, it is likely the Springbok Sandstone has been effectively isolated from the overlying Condamine Alluvium in Tipton 202. Therefore, other data collected from Tipton 202 are considered representative and fit for purpose.

EC data (laboratory data and field measurements where no laboratory data is available) collected to date is shown in Figure 3-10. The data show EC levels in the monitoring bores are generally stable with an increasing trend in Stratheden-63.

The collected pH data are presented in Figure 3-11, showing that pH levels in the monitoring bores are generally stable with a slight declining trend in Stratheden-63.






Figure 3-10: Springbok Sandstone electrical conductivity



Figure 3-11: Springbok Sandstone pH

Metals, major ions and other key analytes

In the analysis of the water quality results, the Queensland Department of Environment and Science (DES) (DES, 2021) recommends a minimum of eight samples at each site be used in the comparison of water quality. In this instance, historical samples from bores have also been combined to statistically analyse

S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 22 of 168




the results into 20th, 50th and 80th percentiles. A comparison of the water quality results for the Springbok Sandstone (the sole formation sampled this reporting period) for analytes listed in the 2021 UWIR along with the relevant water quality guideline values are shown in Appendix B.

Springbok Sandstone

Water quality data is obtained from three bores (Plainview 36, Strathedan-63, and Tipton 202) within the Springbok Sandstone, however Tipton 202 has limited data and thus is insufficient to comment on the statistical results for this bore separately. The water quality results and statistical summary for Springbok Sandstone are provided in Appendix B. The water quality results for chloride 20th and 50th percentiles, magnesium for the 20th percentile, sodium for the 20th and 50th percentiles and sulphate for 20th and 80th percentiles are higher than the aquatic ecosystem value (Appendix B). Concentrations for chloride, sodium and TDS were also exceeded for drinking water guidelines and TDS for stock watering.

Key time series plots were developed for analytes exceeding guidelines criteria. Figure 3-12 shows fluctuations in calcium concentrations at Stratheden-63: concentrations in the two samples taken at Plainview-36 were similar to previous samples at this bore. Chloride concentrations at Stratheden-63 (>1,000 mg/L) are significantly higher than that at Plainview-36 (around 200 mg/L) as shown in Figure 3-13. Figure 3-14 illustrates that concentrations of magnesium are more similar between the two bores with the last readings at the bores only being different by 4 mg/L. Similar to chloride, sodium concentrations are much higher in Stratheden-63 (>600 mg/L) than that at Plainview-36 (around 300 mg/L) as shown in Figure 3-15. Sulphate concentrations are guite variable in Stratheden-63 (Figure 3-16) but are much lower at Plainview 36 (around detection limit of 1 mg/L). Total Dissolved Solids also display a large degree of difference between these two bores, with a difference of greater than 1,500 mg/L (Figure 3-17). It can be observed from water quality time series plots that all peak concentrations at Stratheden-63 occurred in 2019 and samples have not been required to be collected from this bore since 2021.





S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 23 of 168






Figure 3-13: Springbok Sandstone: Chloride



Figure 3-14: Springbok Sandstone: Magnesium




Figure 3-15: Springbok Sandstone: Sodium



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 24 of 168




Figure 3-16: Springbok Sandstone: Sulphate




Figure 3-17: Springbok Sandstone TDS



Chemical composition

The chemical composition of samples collected since 2017 from each of the geological formations is presented in Figure 3-18 to Figure 3-23 as Piper diagrams to highlight the similarities and differences in the proportions of major ions in groundwater from the various formations.

No major ion data was required to be collected for the Condamine Alluvium during this annual reporting period. The Condamine Alluvium piper diagram (Figure 3-18) shows all bores except for Carn Brea-17 are predominantly sodium-chloride type water with carbonate-bicarbonate contributions and a magnesium and calcium contribution in Tipton-195. The chemical composition of samples collected from Carn Brea-17 indicate it is a magnesium-bicarbonate type water.

There is either no trend or a clustered recurring trend in chemical composition evident in all bores except for Wyalla-16 which shows a steady increasing carbonate-bicarbonate contribution.




Figure 3-18: Condamine Alluvium Piper Diagram

No major ion data was required to be collected for the Westbourne Formation monitoring point (Daandine-124) (Figure 3-19) during this annual reporting period. Data previously collected shows it is sodium-chloride type water with no trend in chemical composition evident over time.






Figure 3-19: Westbourne Formation Piper Diagram

The major ion data for the Springbok Sandstone monitoring point Stratheden-63 (Figure 3-20) show it is sodium-chloride type water and there is a recurring trend in the calcium to sodium ratio evident over time. The chemical composition of Plainview 36 shows it is sodium-bicarbonate type water and there is no trend in the data. Two samples from this monitored formation at Plainview 36 were collected during this reporting period, having similar chemical composition to previous samples collected at this location. Three samples were collected from Tipton 202 during the reporting period, which shows the groundwater was initially calcium, magnesium-chloride type water then plots as sodium-chloride type water. As discussed earlier in this report, groundwater at Tipton 202 is likely influenced by cement grout ingress to the gravel pack, which may explain the differences in major ion composition observed in samples collected from this bore relative to other samples from the Springbok Sandstone.



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 27 of 168




Figure 3-20: Springbok Sandstone Piper Diagram

No major ion data was required to be collected for the WCM monitoring points (Figure 3-21) during this annual reporting period. Data previously collected shows Tipton-197 is sodium-chloride type water with a carbonate-bicarbonate contribution, and Carn Brea-18 is a sodium-bicarbonate type water. There is no trend evident in chemical composition in Tipton-197 while Carn Brea-18 is displaying a steady increasing carbonate-bicarbonate and decreasing chloride contributions over time.






Figure 3-21: WCM Piper Diagram

No major ion data was required to be collected for the Hutton Sandstone monitoring points (Figure 3-22) during this annual reporting period. Data previously collected show the Hutton comprises sodium-bicarbonate type water. There is a recurring trend in the calcium to sodium ratio evident over time in Carn Brea-19, and a recurring trend in the bicarbonate to chloride ratio evident over time in Daandine-121.




Figure 3-22: Hutton Sandstone Piper Diagram



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 29 of 168

No major ion data was required to be collected for the Precipice Sandstone monitoring points (Figure 3-23) during this annual reporting period. Data previously collected show Wyalla-17 is sodium-chloride type water with a carbonate-bicarbonate contribution, and Carn Brea-20 is a sodium-bicarbonate type water. There is no trend evident in chemical composition in Wyalla-17 while Carn Brea-20 is displaying a slight but steady increasing chloride contribution over time.




Figure 3-23: Precipice Sandstone Piper Diagram

Trend analysis

Mann-Kendall trend analysis has been undertaken to evaluate increasing and decreasing trends in concentrations for monitored water quality parameters (with more than four data points). Water quality samples were only collected within the Springbok Sandstone (Plainview 36) during the current annual reporting period and thus only a summary from this bore is provided in Figure 3-24 (trend analysis for the other formations can be found in the previous annual report). Although samples were collected from Springbok Sandstone monitoring bore Tipton 202 during the current reporting period, the number of samples (3) is currently insufficient for Mann-Kendall trend analysis; trends in water quality from this bore will be analysed in future reports. The axis on the charts indicates the number of analytes, within that formation, with an observed increasing (positive number) or decreasing (negative number) trend in the analyte concentration. A zero number represents no trend in the data.

For the Springbok Sandstone, the analysis is based on 6 samples at Plainview 36. The data displays there is either an increasing trend, decreasing trend or no trend. Decreasing trends were recorded for carbonate alkalinity, DO (field), pH (field), Redox (field), fluoride, potassium and total alkalinity.

The magnitude of trends for individual monitoring points are presented in Appendix C for monitoring points sampled during this reporting period.






Figure 3-24: Summary of Mann-Kendall trend analysis for Springbok Sandstone monitoring bore Plainview 36

3.3 Ground movement monitoring

Coal seam gas occurs within coal formations through adsorption to the surface of the coal under hydrostatic pressure. Depressurisation of the coal seams below a threshold by groundwater extraction reduces hydrostatic pressure and liberates the gas from the formation. As the pressure falls, the gas migrates to the extraction wells. This process requires substantial lowering of groundwater pressure.

At any point below the ground surface, the weight of overlying strata is supported partly by water pressure and partly by the fabric of the rock mass. Any reduction in water pressure therefore results in an increased proportion of the load being carried by the rock mass, leading to compression of the rock. This is known as an increase in effective stress. The combined compression over the thickness of rock strata affected by reduced water pressure will result in some compaction of the coal seams and may cause overlying formations to subside, resulting in some subsidence at the ground surface.

The development of a CSG field, where the effect of depressurisation of individual wells interact with each other over time, results in relatively uniform depressurisation within a field and a depressurisation surface which gradually



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 31 of 168

decreases away from the CSG field. Any CSG induced ground surface movement is normally expected to be regionally consistent and, with the magnitudes predicted, unobtrusive in terms of environmental and land use impacts. However, monitoring systems have been established to distinguish any significant ground surface movement as a result of CSG operations from natural ground surface changes, such as attrition and climatic induced soil swelling and depletion.

During the previous reporting period OGIA developed a 3D numerical model coupling geomechanics to groundwater depressurisation, predicting magnitude of subsidence and change in slope as a result of CSG operations in the area of the Condamine Alluvium, and developed an analytical model predicting magnitude of subsidence in the greater Surat Basin, as reported in the 2021 UWIR (OGIA, 2021).


The 3D numerical geomechanical model was built incorporating all available data on local geomechanical properties and lithological distribution, with predicted depressurisation from the OGIA groundwater model used as an input to make predictions of subsidence. A model grid ranging from 250 by 250m to 750 by 750m with 88 vertical lavers was used to account for variations in lithology, and OGIA generated a set of 1,000 models from stochastic realisations of geomechanical properties to explore the range of uncertainty in predictions. History matching these models to the available Interferometric Synthetic Aperture Radar (InSAR) data in the vicinity of the Condamine Alluvium allowed the 50 best fitting models to be selected to generate predictions of subsidence. Predicted subsidence and change in slope are therefore reported statistically in the 2021 UWIR as a median (P50) prediction derived from those 50 model runs. Predicted subsidence from the 2021 UWIR, including predicted temporal development of subsidence at specific locations, is presented in Figure 3-25, with predicted maximum changes in slope within the cropping areas of the Condamine River floodplain at any time during CSG field development presented in Figure 3-26.

OGIA processed outputs from the uncertainty analysis to derive probability of magnitudes of subsidence and slope occurring at each model cell. This is presented as maps of the probability of 0.001% (0.01m in 1km) and 0.005% (0.05m in 1km) slope change, together with probability of 100mm and 150mm magnitude subsidence occurring within the cropping areas of the Condamine River floodplain, in Figure 3-27. The Horrane Fault is a large north-south trending fault zone east of Cecil Plains, with displacement of up to approximately 100m. Displacement of the fault and the low permeability of the fault core can result in differential depressurisation patterns either side of the fault, resulting in the greatest predicted change in slope across the Horrane Fault.

During this reporting period, OGIA published a report on coal shrinkage (Aghighi, H, et. al. 2023). Coal shrinkage is the reduction in coal volume due to the extraction of gas. Coal shrinkage contributes to the total subsidence observed at the surface and is implicitly represented in OGIAs prediction model (Aghighi, H, et. al. 2023, p21).



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 32 of 168



OGIA2021_221_2_R

Figure 3-25: 2021 UWIR predicted long-term CSG-induced subsidence across the Surat Basin (after OGIA, 2021)



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 33 of 168





Figure 3-26: Predicted maximum change in ground slope from CSG-induced subsidence within the Condamine Alluvium area (after OGIA, 2021)





OGIA2021_381_5_R

Figure 3-27: Probabilities of predicted subsidence and resulting change in slope within the Condamine Alluvium area (after OGIA, 2021)



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 35 of 168

Data collection

Monitoring of subsidence was carried out by Altamira using satellite borne InSAR, a radar technique used in geodesy and remote sensing (Altamira, 2016), which provides change in ground elevation over time.

Arrow has acquired InSAR data since 2006, with the most recent satellite system (Sentinel) providing data since 2015. The Sentinel satellite system passes every 12 days (every 6 days since 2017) providing high frequency ground motion monitoring, with a vertical resolution to approximately 1mm.

The InSAR data provides a baseline from which future data can be assessed to determine changes in vertical ground elevation, and also provides a snapshot of current vertical ground movement.

Geotechnical ground movement monitoring points have also been installed to provide a ground-truthing check of the InSAR data. These points are instrumented with Global Navigation Satellite System (GNSS) Continually Operating Reference Stations (CORS), and provide millimetric accuracy of changes in vertical elevation.

Periodic surveys using Light Detection And Ranging (LiDAR), a remote-sensing technique using airborne laser scanning systems, have been undertaken to provide snapshots of relative elevation of the land and derived slopes at moment of capture. These surveys, which provide for accurate assessment of slopes at property and regional scale, have been acquired for Arrow in 2012, 2014, 2020, 2021, 2022 and 2023. The LiDAR data provides a temporal baseline from which future data can be assessed to determine changes in slope.

These monitoring methods detect changes in the ground surface from all potential causes, not just CSG induced subsidence.

Data analysis

Following the baseline InSAR survey for the period 2006 to 2015, and reported in the Stage 1 WMMP, Tre-Altamira was commissioned for ongoing surface deformation monitoring across the Arrow tenements, with the latest data available up to the end of June 2023.

Figure 3-28 shows a down-sampled data set, where the point cloud InSAR data was reduced to the median vertical velocity within a 1,000 m x 1,000 m grid. Stable has been classified as ground motion of less than 8 mm per year (subsidence or uplift) as related to the screening level identified in the Stage 1 WMMP.

These data show stability across most of Arrow's tenure, together with areas of downward ground movement, majority of which being away from areas of gas production. Areas of downward ground movement are particularly observed over the vertosol soils of the Condamine Alluvium, and are likely related to decreased rainfall observed over the monitoring period, compared to previous, causing shrinkage of the clay soils. Areas of poor satellite data coherence, with only a small number of InSAR points per square km, also occur within the area of the Condamine Alluvium. Coherence is a measure of the local spatial correlation between radar images, where changes to the reflection of the radar signal (such as due to rapid vegetation growth or changes in soil moisture) result in irregular variation in phase and higher noise in the data.



As shown below, 243 of the (1km x 1km) cells had recorded downward ground movement in excess of the screening level of 8 mm per year for more than 50% of the coherent InSAR points within those cells. Of these, 66 of these grid cells located within 4.5km of Arrow producing wells (the reasonable distance within which CSG induced subsidence might be detectable). As these 66 areas exceeded the screening level, further assessment of changes to the ground surface and slopes within and around the grid cell areas was undertaken, using the InSAR point clouds and LiDAR surveys, to assess if there was any CSG induced subsidence impacts and exceedance of investigation levels.






Figure 3-28: InSAR Median Ground Movement (July 2022 to June 2023 inclusive)

arrowenergy go further

S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 38 of 168

A process was undertaken considering areal slope change on a 250m resolution grid, as well as investigation of the number of 2D InSAR points per cell. For grid cells with less than 5 valid 2D InSAR points, persistent scatter points from line of site (ascending and descending satellite) data were preferentially adopted. Overall, it was determined that 34 of the 66 grid cells had areal slope change (LiDAR derived) in excess of 0.001m/m and over 50% of InSAR points with vertical movement greater than 8mm/yr. These 34 cells were investigated further to validate if investigation levels had actually been exceeded due to CSG activity.

Transects were taken along structural and natural features within the cells, the location and results of these are summarised in Appendix E. Of the 156 transects taken across the 34 grid cells, 3 exceeded the investigation level of 0.001 m/m (0.1%). On further inspection of those locations, it was apparent that the slope change recorded was isolated and due to causes other than CSG, as summarised below. Therefore, no site specific investigations or trigger threshold exceedance action plans were required or initiated from the assessment or during the reporting period.

Transect 3 taken in grid 2039 was found to exceed 0.001m/m slope change. The location and profile are shown in Figure 3-29 and Figure 3-30 respectively.



Figure 3-29: 1x1km Grid Cell ID 2039 showing location of transects under






Figure 3-30: Profile of Transect 3 on Grid Cell ID 2039

As shown above, there was vertical movement exceeding 150mm vertically along the majority of the transect. Considering the vicinity of Gilgai visible in the image, the short length of the transect and that no other profiles experienced material slope change in the area, it is concluded that this slope change is localised and due to natural causes.

Transect 1 taken in grid 2571 was found to exceed 0.001m/m slope change. The location and profile are shown in Figure 3-31 and Figure 3-32 respectively.








Figure 3-31: 1x1km Grid Cell ID 2571 showing location of transects undertaken

Figure 3-32: Profile of Transect 1 on Grid Cell ID 2571

As shown above, there was vertical movement exceeding 400mm vertically at the end of the transect, which is unprecedented for CSG induced subsidence. Water ponding is also visible in the imagery at this same end point of the transect. There is apparent surface variability detected in the 2023 DEM compared to 2022 where the profile enters heavy bushland. It can be observed that there is no material slope change in the transect from chainage 0-180m along the roadway and through open grassland. The remaining transects in this cell did not experience material slope change. It is therefore concluded that material slope change has not occurred at this transect due to CSG, and rather it is due to variability between DEMs caused by a combination of vegetation and/or ponded water.

Transect 5 taken in grid 2346 was found to exceed 0.001m/m slope change. The location and profile are shown in Figure 3-33 and Figure 3-34 respectively.






Figure 3-33: 1x1km Grid Cell ID 2346 showing location of transects undertaken




Figure 3-34: Profile of Transect 5 on Grid Cell ID 2346

As shown above, there was vertical movement exceeding 800mm vertically at the start of the transect, which is unprecedented for CSG induced subsidence. The profile was taken along a drainage channel, and considering the profile in 2022 was relatively level, it is likely that this drainage channel was holding water in the 2022 LiDAR flight. The remaining transects in this cell did not experience



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 42 of 168 material slope change. It is therefore concluded that this slope change is isolated and due to changes in water levels along the drainage line.

3.4 Update to monitoring network

Groundwater monitoring locations and frequency of monitoring were revised upon the release of the 2021 UWIR in line with Section 7.3 of the SGP Updated WMMP. The monitoring network presented in Table 7-1 of the SGP Updated WMMP has been aligned with the 2021 UWIR water monitoring strategy (WMS) to ensure monitoring is undertaken proportionally to the predicted impacts presented in the 2021 UWIR. A summary of the changes to the monitoring network is provided in Table 5 and the updated list of monitoring points (and their purpose) is provided in Table 6 and illustrated in Figure 3-35 and Figure 3-36. In addition to the changes noted in Table 5, the groundwater chemistry suite and sampling frequency have been revised to align with 2021 UWIR and is presented in Table 7.

Key changes to the monitoring programs are:

- the number of monitoring points has increased from 120 in the SGP Updated WMMP to 150 to align with the 2021 UWIR,
- the groundwater analysis suite has been expanded to include strontium isotopes (87Sr/86Sr) (this was changed under the 2019 UWIR),
- Table 4-2 of the 2021 UWIR supporting document "Details of the Water Monitoring Strategy for the Underground Water Impact Report 2021" (OGIA 2021b) (and also Table H-4 of the 2019 UWIR) stipulates a groundwater sampling frequency of every six months until five samples have been obtained, with one of these samples analysed for dissolved strontium and strontium isotopes (⁸⁷Sr/⁸⁶Sr) in Springbok Sandstone, Hutton Sandstone and Precipice Sandstone monitoring points.



Report

Table 5: Summary of changes to the Updated CSG WMMP monitoring points to align with the 2021 UWIR monitoring requirements

Location ID	Target Aquifer		nonitoring rec	quirement as per WMMP	2021 UWIR Monitoring Requirement	Monitoring poin
		Level / pressure	Water Quality	CA-WCM flux		
Bora Creek-10	WCM	\checkmark			No change. Still required to be monitored for the 2021 UWIR.	Monitoring point
Burunga Lane-174	Evergreen	\checkmark			No change. Still required to be monitored for the 2021 UWIR.	
Burunga Lane-174	Precipice	\checkmark	\checkmark		No change to the pressure monitoring requirement. Water quality monitoring requirement has been removed from the 2021 UWIR.	Access to the si ongoing negoti
Burunga Lane-176	Hutton	\checkmark	\checkmark		No change. Still required to be monitored for the 2021 UWIR.	Monitoring as p
Burunga Lane-176	WCM	\checkmark				water quality mo
Carn Brea-17	Condamine Alluvium	✓	✓	~	No change to the level monitoring requirement. Water quality monitoring is no longer required as sufficient number of samples have been collected as per Table 9-4 of the 2021 UWIR.	Monitoring as p water quality mo
Carn Brea-18	WCM	√	✓ (atUWIR MP41 only)	~	No change to the pressure monitoring requirement. Water quality monitoring is no longer required as sufficient number of samples have been collected as per Table 9-4 of the 2021 UWIR.	Monitoring as p water quality mo
Carn Brea-19	Evergreen	\checkmark			No change to the pressure monitoring requirement.	М
Carn Brea-19	Hutton	√	✓		No change to the pressure monitoring requirement. Water quality monitoring is no longer required as sufficient number of samples have been collected as per Table 9-4 of the 2021 UWIR.	Monitoring as p water quality mo
Carn Brea-20	Precipice	\checkmark	√		No change to the level monitoring requirement. Water quality monitoring requirement has been removed from the 2021 UWIR.	Monitoring as p wate
Carn Brea-21	WCM	✓		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	М
Carn Brea-23	Condamine Alluvium	√		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	М
Carn Brea-24	CA / WCM transition layer	√		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	М
Castledean-18	Springbok	✓			No change. Still required to be monitored for the 2021 UWIR.	Monitoring poir M
Castledean-18	WCM	~			No change. Still required to be monitored for the 2021 UWIR.	М
Daandine-121	Hutton	✓	✓		No change to the pressure monitoring requirement. Water quality monitoring is no longer required as sufficient number of samples have been collected as per Table 9-4 of the 2021 UWIR.	Monitoring as p water quality mo
Daandine-123	WCM	\checkmark			Not listed to be monitored for the 2021 UWIR.	Monitorir
Daandine-124	Westbourne	~	✓		No change to the level monitoring requirement. Water quality monitoring requirement has been removed from the 2021 UWIR.	Monitoring as p wate
Daandine-134	WCM	✓			No change. Still required to be monitored for the 2021 UWIR.	М
Daandine-134	Eurombah	\checkmark			No change. Still required to be monitored for the 2021 UWIR.	Μ



bint status and current monitoring requirement based on 2021 UWIR

int operational. Monitoring as per Updated CSG WMMP. site was not possible during the reporting period due to otiations with the landholder. The monitoring points are currently offline. s per Updated CSG WMMP except for the cessation of monitoring in Burunga Lane-174 (removed from UWIR). Monitoring point operational. s per Updated CSG WMMP except for the cessation of nonitoring (completion of collection of five samples in Q4 2020). Monitoring point operational. s per Updated CSG WMMP except for the cessation of nonitoring (completion of collection of five samples in Q4 2020). Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. s per Updated CSG WMMP except for the cessation of nonitoring (completion of collection of five samples in Q4 2020). Monitoring point operational. s per Updated CSG WMMP except for the cessation of ater quality monitoring (removed from UWIR). Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. Monitoring as per Updated CSG WMMP. oint is operational but dry. Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. s per Updated CSG WMMP except for the cessation of nonitoring (completion of collection of five samples in Q4 2020). Monitoring point operational. pring is no longer required under the 2021 UWIR. Monitoring point operational. s per Updated CSG WMMP except for the cessation of ater quality monitoring (removed from UWIR). Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. Monitoring as per Updated CSG WMMP.

Location ID	Target Aquifer		onitoring recoded	quirement as per WMMP	2021 UWIR Monitoring Requirement	Monitoring point status and current monitoring requirement based on 2021 UWIR
		Level / pressure	Water Quality	CA-WCM flux		
Daandine-161	Condamine Alluvium	\checkmark		√	No change. Still required to be monitored for the 2021 UWIR.	No monitoring data available for Daandine-161 as bore was isolated by standing water during monitoring events.
Daandine-163	CA / WCM transition layer	\checkmark		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Daandine-164	WCM	\checkmark		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Daandine-254	WCM	\checkmark			No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Daandine-263	WCM	✓			No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Daandine-264	WCM	\checkmark			No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Dundee-20	WCM	\checkmark		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	Monitoring as per Updated CSG WMMP.
Glenburnie-19	WCM	\checkmark			No change. Still required to be monitored for the 2021 UWIR.	Pressure gauge had failed. Pressure gauge became operational again in June 2022.
Hopeland-17	Springbok	✓			No change. Still required to be monitored for the 2021 UWIR.	Monitoring as per Updated CSG WMMP. Monitoring point operational. Monitoring as per Updated CSG WMMP.
Hopeland-17	WCM	✓			No change. Still required to be monitored for the 2021 UWIR.	Periods of no data (between April and June 2022) within the annual period within bores monitoring the WCM and jumps in recorded levels. Data validation ongoing to confirm observed pressure trends.
Kedron-570	Eurombah	√			No change. Still required to be monitored for the 2021 UWIR.	Monitoring as per Updated CSG WMMP. Monitoring point operational.
Kedron-570	Hutton	\checkmark			No change. Still required to be monitored for the 2021 UWIR.	Monitoring as per Updated CSG WMMP. Monitoring point operational.
Kedron-570	WCM	\checkmark			No change. Still required to be monitored for the 2021 UWIR.	Monitoring as per Updated CSG WMMP. Monitoring point operational. Monitoring as per Updated CSG WMMP.
Kedron-570	Springbok	\checkmark			Monitoring point removed from the previous UWIR (2019).	Monitoring point no longer monitored as per the 2019 and 2021 UWIRs.
Kogan North-56	WCM	\checkmark		~	Monitoring point removed from the 2021 UWIR (previously removed in 2019 UWIR).	Monitoring point no longer monitored as per the 2021 UWIR (previously removed in 2019 UWIR)
						Monitoring point plugged and abandoned.
Kogan North-79	CA / WCM transition layer	✓		~	Monitoring point removed from the 2021 UWIR (previously removed in 2019 UWIR).	Monitoring point no longer monitored as per the 2021 UWIR.
Kogan North-79	Condamine Alluvium	\checkmark		\checkmark	Monitoring point removed from the 2021 UWIR (previously removed in 2019 UWIR).	Monitoring point no longer monitored as per the 2021 UWIR.
Tipton-153	Hutton	✓			No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Long Swamp-1 (replaced by Longswamp 27)	WCM	\checkmark			Monitoring point replaced by Longswamp 27 installed adjacent to Long Swamp- 1.	Monitoring point (Longswamp 27) operational. Monitoring as per Updated CSG WMMP.
Longswamp-7	WCM	✓			No change. Still required to be monitored for the 2021 UWIR.	Period of no monitoring data (between February and March 2022) in annual period. Monitoring point operational. Monitoring as per Updated CSG WMMP.
Macalister-5	Condamine Alluvium	\checkmark		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Macalister-8	WCM	\checkmark		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.



Location ID	Target Aquifer		onitoring recoded	quirement as per WMMP	2021 UWIR Monitoring Requirement	Monitoring point
		Level / pressure	Water Quality	CA-WCM flux		
Meenawarra-21	Springbok	✓			No change. Still required to be monitored for the 2021 UWIR.	М
Meenawarra-21	WCM	✓			No change. Still required to be monitored for the 2021 UWIR.	М
Meenawarra-5	WCM	\checkmark			Monitoring point removed from the 2021 UWIR.	Monitoring
Pampas-18	Condamine Alluvium	✓		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	М
Pampas-5	WCM	✓		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	М
Plainview-35	WCM	\checkmark			No change. Monitoring point replaced previous UWIR monitoring point Plainview-1.	M
Plainview-25	CA / WCM transition layer	✓		\checkmark		
Plainview-25	Condamine Alluvium	\checkmark		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	
Plainview-25	WCM	\checkmark		\checkmark		Μ
RN 41620043	WCM (previously assessed by OGIA as Springbok Sandstone)	√			No change. Still required to be monitored for the 2021 UWIR.	М
RN 42230088	Condamine Alluvium	✓		\checkmark	Monitoring point removed from the 2021 UWIR.	Monitoring
RN 42230209	Condamine Alluvium	~	✓	~	No change to the level monitoring requirement. Water quality monitoring is no longer required as sufficient number of samples have been collected as per Table 9-4 of the 2021 UWIR.	Monitoring as p water quality mo
RN 42231294	Condamine Alluvium	√		\checkmark	Monitoring point removed from the 2021 UWIR.	Monitoring poin
RN 42231295	WCM	✓		\checkmark	Monitoring point removed from the 2021 UWIR.	Monitoring poin
RN 42231339	Condamine Alluvium	√			Monitoring point removed from the 2021 UWIR.	Monitoring poin
RN 42231370	Condamine Alluvium	~	√		No change to the level monitoring requirement. Water quality monitoring is no longer required as sufficient number of samples have been collected as per Table 9-4 of the 2021 UWIR	Monitoring as p water quality mo
RN 42231463	Condamine Alluvium	~		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	М
Stratheden-63	Springbok	~	✓		No change to the level monitoring requirement. Water quality monitoring is no longer required as sufficient number of samples have been collected as per Table 9-4 of the 2021 UWIR	Monitoring as p water quality mo 2020, and coll
Tipton-157	WCM	~			No change. Still required to be monitored for the 2021 UWIR.	Μ
Tipton-195	Condamine Alluvium	V	√	✓	No change to the level monitoring requirement. Water quality monitoring is no longer required as sufficient number of samples have been collected as per Table 9-4 of the 2021 UWIR	Monitoring as p water quality mo
Tipton-196A	CA / WCM transition layer	✓		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	
						M



bint status and current monitoring requirement based on 2021 UWIR

Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. Monitoring as per Updated CSG WMMP. g point no longer monitored as per the 2021 UWIR. Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring points operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. Monitoring as per Updated CSG WMMP. g point no longer monitored as per the 2021 UWIR. Monitoring point operational. s per Updated CSG WMMP except for the cessation of nonitoring (completion of collection of five samples in Q4 2020). pint no longer required to be monitored as per the 2021 UWIR. oint no longer required to be monitored as per the 2021 UWIR. oint no longer required to be monitored as per the 2021 UWIR. Monitoring point operational. s per Updated CSG WMMP except for the cessation of nonitoring (completion of collection of five samples in Q4 2020). Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. s per Updated CSG WMMP except for the cessation of nonitoring (completion of collection of five samples in Q4 collection of samples for analysis of strontium isotopes completed in Q4 2021). Monitoring point operational. Monitoring as per Updated CSG WMMP. Monitoring point operational. s per Updated CSG WMMP except for the cessation of nonitoring (completion of collection of five samples in Q4 2020). Monitoring point operational. Monitoring as per Updated CSG WMMP.

Location ID	Target Aquifer		onitoring req	uirement as per WMMP	2021 UWIR Monitoring Requirement	Monitoring point status and current monitoring requirement based on 2021 UWIR
		Level / pressure	Water Quality	CA-WCM flux		
Tipton-197	WCM	~	 ✓ (at UWIR MP 89 only) 	~	No change to the level monitoring requirement. Water quality monitoring is no longer required as sufficient number of samples have been collected as per Table 9-4 of the 2021 UWIR	Monitoring point operational. Monitoring as per Updated CSG WMMP except for the cessation of water quality monitoring (completion of collection of five samples in Q4 2020).
Tipton-204	CA / WCM transition layer	\checkmark		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Tipton-204	Condamine Alluvium	√		~	No change. Still required to be monitored for the 2021 UWIR.	Monitoring as per Opdated COC WMMP. Monitoring point operational. Monitoring as per Updated CSG WMMP.
Tipton-204	WCM	√		✓	No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Tipton-206	Eurombah	\checkmark			No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Tipton-206	WCM	✓		✓	No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Tipton-221	Condamine Alluvium	✓		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Tipton-222	CA / WCM transition layer	✓		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Macalister 7	Condamine Alluvium	✓		\checkmark	No change. Still required to be monitored for the 2021 UWIR	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Macalister 6	WCM	✓		\checkmark	No change. Still required to be monitored for the 2021 UWIR	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Macalister 6	Eurombah	~			No change. Still required to be monitored for the 2021 UWIR	Monitoring point operational. Monitoring as per Updated CSG WMMP.
Wyalla-17	Hutton	~			No change. Still required to be monitored for the 2021 UWIR	Monitoring point operational. Monitoring as per Updated CSG WMMP.
UWIR Site 94	Hutton	\checkmark			Monitoring point not yet installed as 2016 UWIR timing requirement for installation (two years prior to production within 10km) was not triggered.	Monitoring point no longer required.
					This monitoring point is no longer required under the 2021 UWIR (previously not required in 2019 UWIR).	
UWIR Site 94 (Burunga Lane 186)	WCM	\checkmark			Monitoring point not yet installed as 2016 UWIR timing requirement for installation (two years prior to production within 10km) was not triggered. The 2019 UWIR requires this monitoring point to be installed in 2022.	Monitoring point is scheduled to be installed in 2022 as per the 2021 UWIR.
Wyalla-16	Condamine Alluvium	V	✓	V	No change to the level monitoring requirement. Water quality monitoring is no longer required as sufficient number of samples have been collected as per Table 9-4 of the 2021 UWIR	Monitoring point operational. Monitoring as per Updated CSG WMMP except for the cessation of water quality monitoring (completion of collection of five samples in Q4 2020).
Wyalla-17	Precipice	~	√		No change to the level monitoring requirement. Water quality monitoring requirement has been removed from the 2021 UWIR	Monitoring point operational. Monitoring as per Updated CSG WMMP except for the cessation of water quality monitoring (completion of collection of five samples in Q4 2020).
Wyalla-18	WCM	\checkmark		\checkmark	No change. Still required to be monitored for the 2021 UWIR.	Monitoring point operational. Monitoring as per Updated CSG WMMP.



Report

Table 6: Revised Updated CSG WMMP Monitoring Network as per the 2021 UWIR WMS

						Mo	onitoring po	<u> </u>	
Location ID	OGIA MP ID	Latitude	Longitude	Target Aquifer	UWIR Required Online Date	Level / pressure	Quality	CA- WCM flux	Early warning
41620043	578	-27.922222	151.121389	WCM	Complete	\checkmark			\checkmark
42230209	281	-26.7422	150.6799	Condamine Alluvium	Complete	\checkmark	\checkmark	\checkmark	✓
42231370	51	-27.491498	151.393194	Condamine Alluvium	Complete	\checkmark	\checkmark		\checkmark
42231463	37	-27.548794	151.313017	Condamine Alluvium	Complete	\checkmark		\checkmark	\checkmark
42231597	597	-27.73082	151.76343	Main Range Volcanics	Complete	\checkmark			
Baking Board 4	877	-26.567	150.653	WCM	2022	\checkmark			
Baking Board 5	891	-26.48009491	150.5512695	Alluvium	2022	\checkmark			
Barakula 2	878 and 869	-26.480094	150.551269	WCM, Hutton Sandstone	2022	\checkmark			
Bora Creek 10	579	-27.924504	151.12492	WCM	Complete	\checkmark			
Burunga Lane 186	494, 495, 496	-26.2301	149.9534	WCM	2022	\checkmark			
Burunga Lane-174	478, 625	-26.242667	150.050176	Precipice, Evergreen	Monitoring points installed. Awaiting land access to recommence monitoring	\checkmark			✓ (478
Burunga Lane-176	473, 474, 475, 476, 477	-26.242897	150.049993	WCM, Hutton	Monitoring points installed. Awaiting land access to recommence monitoring	\checkmark	✓ (477)		✓ (470
Carn Brea 21	94	-27.437622	151.357504	WCM	Complete	\checkmark		\checkmark	
Carn Brea 22	882	-27.43779	151.357466	Hutton	2022	\checkmark			
Carn Brea 23	92	-27.43762778	151.3576733	Condamine Alluvium	Complete	\checkmark		\checkmark	✓
Carn Brea 24	93	-27.437628	151.357707	Condamine Alluvium - Walloon Transition Layer	Complete	\checkmark		\checkmark	
Carn Brea-17	38	-27.533016	151.36648	Condamine Alluvium	Complete	\checkmark	\checkmark		\checkmark
Carn Brea-18	40, 41, 42, 43	-27.532995	151.36633	WCM	Complete	\checkmark	✓ (41)	\checkmark	
Carn Brea-19	44, 45, 46	-27.532975	151.36618	Hutton, Evergreen	Complete	\checkmark	✓ (45)	\checkmark	✓ (44)
Carn Brea-20	47	-27.532954	151.36603	Precipice	Complete	\checkmark	\checkmark		✓
Castledean-18	375, 376, 377, 378	-26.552914	150.221984	WCM, Springbok	Complete	\checkmark			✓ (37)
Daandine 263	181	-27.102426	150.961255	WCM	Complete	\checkmark			
Daandine 264	148	-27.15307149	151.0442114	WCM	Complete	\checkmark			
Daandine-121	182	-27.100415	150.955656	Hutton	Complete	\checkmark	\checkmark		\checkmark
Daandine-123	719, 720	-27.144075	150.948059	WCM, Precipice	Complete	\checkmark			
Daandine-124	157	-27.144119	150.948001	Westbourne Formation	Complete	\checkmark			
Daandine-134	162, 163, 164	-27.14401378	150.9485653	Tangalooma Sandstone, Eurombah, WCM	Complete	\checkmark			
Daandine-161	166	-27.118534	151.075606	Condamine Alluvium	Complete	\checkmark		\checkmark	\checkmark
Daandine-163	167	-27.119974	151.075875	Condamine Alluvium - Walloon Transition Layer	Complete	\checkmark		\checkmark	
Daandine-164	168	-27.120008	151.075969	WCM	Complete	✓		\checkmark	
Daandine-254	160, 161, 159	-27.144104	150.948239	WCM	Complete	\checkmark			
Dundee-20	283, 284, 285	-26.743476	150.678351	WCM	Complete	\checkmark		\checkmark	
Glenburnie 19	23	-27.639218	151.167664	WCM	Complete	✓			
Glenburnie 20	732	-27.83304667	151.0972642	Springbok	Complete	\checkmark			
Glenburnie 21	733	-27.83242474	151.0980474	WCM	Complete	\checkmark			
Glenburnie 22	734	-27.83252476	151.0981482	WCM	Complete	\checkmark			
Glenburnie-18	735, 736, 737, 738, 739	-27.72017464	151.1565154	Hutton, WCM, Springbok	Complete	✓	✓ (739)		
Hopeland-17	615, 616, 617, 618	-26.973208	150.611817	Springbok, WCM	Complete	✓	× 7		✓ (61
	626, 627, 628, 629			WCM, Tangalooma Sandstone, Hutton	1 1 1 1	\checkmark			√ (62





						Mo	onitoring po	oint purp	ose
Location ID	OGIA MP ID	Latitude	Longitude	Target Aquifer	UWIR Required Online Date	Level / pressure	Quality	CA- WCM flux	Early warning
Kogan North-79	747, 748, 749	-26.99886636	150.9018044	WCM	Complete	\checkmark			
Lone Pine-14	750	-27.55472483	151.3591434	WCM	Complete	\checkmark			
Lone Pine-16	751	-27.55468423	151.3587845	WCM	Complete	\checkmark			
Long Swamp 27	83	-27.343091	151.124186	WCM	Complete	\checkmark			
Longswamp 28	752	-27.3415143	151.0917476	Westbourne Formation	Complete	\checkmark			
Longswamp 29	753	-27.34150399	151.0915948	Springbok	Complete	\checkmark			
Longswamp 30R	754	-27.34148851	151.0914061	WCM	Complete	\checkmark			
Longswamp 31	755	-27.34347302	151.0957158	Condamine Alluvium	Complete	\checkmark			
Longswamp 33	756	-27.26852415	151.0953309	Springbok	Complete	\checkmark			
Longswamp 34	757	-27.26851019	151.0952109	WCM	Complete	\checkmark			
Longswamp-7	145, 146, 147	-27.184333	151.127397	WCM	Complete	\checkmark			
Macalister 5	244	-26.895087	150.954269	Condamine Alluvium	Complete	\checkmark		✓	✓
Macalister 6	205, 206	-27.025681	151.133187	Eurombah Formation, WCM	Complete	\checkmark		✓	
Macalister 7	203	-27.025639	151.133279	Condamine Alluvium	Complete	✓		✓	✓
Macalister 8	245	-26.895103	150.954439	WCM	Complete	✓		\checkmark	
Meenawarra-21	34, 35, 36, 619	-27.57994613	151.1333987	WCM, Springbok	Complete	✓			✓ (619)
Mt Haystack 2	598	-27.727166	151.763337	WCM	Complete	✓			
Mt Haystack 4	600	-27.724061	151.276431	WCM	Complete	✓			
Mt Haystack 5	599	-27.723972	151.276483	Condamine Alluvium	Complete	✓			
Pampas 18	24	-27.61473529	151.2266555	Condamine Alluvium	Complete	\checkmark		\checkmark	\checkmark
Pampas-5	25	-27.614646	151.226669	WCM	Complete	✓		\checkmark	
Plainview 34	1053,1054	-27.3828	151.1869	WCM	Complete	\checkmark			
Plainview 35	77	-27.3842	151.2044	WCM	Complete	✓			
Plainview 36	789, 790	-27.3868	151.216	Springbok	Complete	✓	✓ (790)		
Plainview 37	791	-27.3868	151.216	Condamine Alluvium	Complete	\checkmark	,		
Plainview-25	119, 120, 121	-27.25210762	151.2922186	Condamine Alluvium, Condamine Alluvium - Walloon Transition Layer, WCM	Complete	\checkmark		~	✓ (119)
Punch Bowl-15	796, 797	-26.55156345	150.3782458	WCM	Complete	\checkmark			
Stratheden-62	822	-27.19895544	151.0267434	Condamine Alluvium	Complete	\checkmark			
Stratheden-63	622, 623	-27.198933	151.026801	Springbok	Complete	\checkmark	✓ (623)		✓ (622)
Tipton 153	620	-27.358607	151.153091	Hutton	Complete	\checkmark			\checkmark
Tipton 200	832, 834, 835, 836	-27.383	151.173	Hutton, WCM	Complete	\checkmark			
Tipton 202	830, 833	-27.383	151.173	Springbok	Complete	\checkmark	✓ (830)		
Tipton 203	831	-27.383	151.173	Condamine Alluvium	Complete	\checkmark			
Tipton 204	149, 150, 151	-27.149552	151.20938	Condamine Alluvium, Condamine Alluvium - Walloon Transition Layer, WCM	Complete	✓		\checkmark	✓ (149)
Tipton 206	141, 142	-27.215683	151.348949	Eurombah, WCM	Complete	\checkmark		\checkmark	
Tipton 221	138	-27.215626	151.348869	Condamine Alluvium	Complete	\checkmark		\checkmark	\checkmark
Tipton 222	139	-27.215589	151.348817	Condamine Alluvium - Walloon Transition Layer	Complete	\checkmark		\checkmark	
Tipton-157	72, 73, 74	-27.398089	151.088923	WCM	Complete	\checkmark			
Tipton-194	861	-27.38748328	151.1181328	Precipice	Complete	\checkmark			
Tipton-195	84, 85	-27.32054	151.20535	Condamine Alluvium	Complete	✓	✓ (85)	\checkmark	✓ (84)





						Mo	nitoring po	oint purp	ose
Location ID	OGIA MP ID	Latitude	Longitude	Target Aquifer	UWIR Required Online Date	Level / pressure	Quality	CA- WCM flux	Early warning
Tipton-196A	86	-27.320232	151.205042	Condamine Alluvium - Walloon Transition Layer	Complete	✓		\checkmark	
Tipton-197	88, 89, 90, 91	-27.320228	151.205316	WCM	Complete	\checkmark	√ (89)	\checkmark	
Plainview 16	792	-27.3858	151.2165	Hutton	Complete	✓			
Punch Bowl 53	868	-26.312681	150.377656	Hutton	2023	✓			
UWIR MP ID 1047	1047	-27.4429	151.2887	Springbok	Timing to be determined by OGIA	✓			
UWIR MP ID 1048	1048	-27.4429	151.2887	WCM	Timing to be determined by OGIA	✓			
UWIR MP ID 1049	1049	-27.4429	151.2887	Condamine Alluvium	Timing to be determined by OGIA	✓			
UWIR MP ID 1050	1050	-27.4822	151.1834	Springbok	Timing to be determined by OGIA	✓			
UWIR MP ID 1051	1051	-27.4822	151.1834	WCM	Timing to be determined by OGIA	\checkmark			
UWIR MP ID 1052	1052	-27.4822	151.1834	Springbok	Timing to be determined by OGIA	✓			
UWIR MP ID 1060	1060	-27.4340	151.2272	Condamine Alluvium	Timing to be determined by OGIA	✓			
UWIR MP ID 1061	1061	-27.4340	151.2272	Springbok	Timing to be determined by OGIA	\checkmark			
UWIR MP ID 1062	1062	-27.4340	151.2272	WCM	Timing to be determined by OGIA	✓			
Wyalla-16	246, 248	-26.86619798	150.7550201	Condamine Alluvium	Complete	✓	✓ (248)	\checkmark	\checkmark
Wyalla-17	252, 624	-26.86632619	150.7549919	Precipice, Hutton	Complete	✓			✓ (252)
Wyalla-18	249, 250, 251	-26.8660577	150.7550667	WCM	Complete	\checkmark		\checkmark	

Notes:

(1) As noted in Revision 0 of the SGP Updated WMMP, the baseline monitoring assessment indicated Condamine Alluvium bores 42231370, Daandine-161 and Carn Brea-17 exhibited regular drawdown and recovery cycles of several metres because of nearby groundwater extraction for agricultural or other non-CSG uses. The magnitude of these groundwater fluctuations is such that these bores have limited use for early warning monitoring, and as such, have been excluded as early warning monitoring bores in the SGP Updated WMMP.




340,000 3000 20,00 Bell Kogan North-79 2 (WCM) 6 Macalister 6 2 (EUR, TCM) Macalister 7 (CAL) Daandine 263 (WCM) Daandine-121 (HS)(WQ) Daandine-161 (CAL) Daandine-164 (WCM) 0 Tipton 200 (HS, 3 WCM) Tipton 202 (SBS)(WQ) Daandine 264 (WCM) 6 • Tipton 204 2 (CAL, TCM) 0 Tipton 203 (CAL) Daandine-123 2 (HS, PS) DALBY Plainview 16 (HS) Congswamp-7 3 (WCM) Tipton 206 2 (EUR, WCM) Daandine-124 (WF) 0 Stratheden-62 (CAL) Stratheden-63 (SBS)(WQ) O-Plainview-25 2 (CAL, WCM) Daandine-134 3 EUR, TS, WCM) Plainview 34 2 Daandine-254 3 (WCM) Tipton-197 2 (WCM) 6980000 (WCM) Plainview 36 Plainview 35 (WCM) Longswamp 33 (SBS) Longswamp 34 (WCM) Longswamp 28 (WF) (SBS)(WQ) Plainview 37 (CAL) Tipton-153 (HS) 00 Longswamp 29 (SBS) Longswamp 30R (WCM) 0000 Carn Brea 22 (HS Longswamp 31 (All)-0 Carn Brea-21 (WCM) Oakey Longswamp 27 (WCM) Tipton-157 3 (WCM) Tipton-194 (PS) Carn Brea-23 (All) Carn Brea-24 (CAL-WCM) New Well ??? 3 (CAL, SBS, WCM) New Well ??? 3 (CAL, SBS, WCM) -RN 42231370 (CAL)(WQ) New Well ??? 3 (CAL, SBS, WCM) Cecil Plains 0 Carn Brea-19 (EVG) Carn Brea-20 (PS) 0 0 Meenawarra-21 (SBS) Lone Pine-14 (WCM) RN 42231463 (CAL) -Lone Pine-16 (WCM) Pampas-5 (WCM) Pampas 18 (CAL) Glenburnie 19 (WCM) - • Mt Haystack 2 (TCM) Glenburnie-18 3 (HS, SBS, WCM) O 0 42231597 (MRV) Glenburnie 21 (WCM) Glenburnie 22 (WCM) Glenburnie 20 (SBS) 920000 6 Legend Millmerran 2021 UWIR Monitoring • Point RN 41620043 (WCM)-. Maior Town Bora Creek 10 (WCM) Arrow Tenure (PL only) All - Alluvium CAL - WCM - Condamine Alluvium - WCM transition layer - WCM transition layer CAL - Condamine Alluvium EVG - Evergreen Formation EVG - Evergreen Formation HS - Hutton Sandstone MRV - Main Range Volcanics PS - Precipice Sandstone SBS - Springbok Sandstone TS - Tangalooma Sandstone WCM - Walloon Coal Measures WF - Westbourne Formation WQ - water quality sampling point 2021 UWIR Arrow Monitoring Network - Southern Tenure Date:3/01/2024 Source: Arrow Energy Pty Ltd Issued To: Arrow Energy Author: Arrow Energy arrow energy Geoscience Australia DNRME Scale 1.600.000 oordinate System: GDA 1994 MGA Zone of Queensland (Department of N onsideration of the State permittin ate gives no warranty in relation the State of Quee 2023. In considera that the Stra ttribution cy or suitability) s... e) for any loss, dan e data. Data must no Note: The dimensions, areas, number of lots, size and location information are approximate only and may vary. NOT FOR CONSTRUCTION

ARROW ENERGY - SURAT GAS PROJECT

Figure 3-35: 2021 UWIR Arrow Monitoring Network – southern tenure



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 51 of 168



ARROW ENERGY - SURAT GAS PROJECT

Figure 3-36: 2021 UWIR Arrow Monitoring Network – northern tenure



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 52 of 168

Suite	Туре	Parameters to be measured as part of the suite	Frequency
Suite A	Field Parameters	Electrical Conductivity (µS/cm @ 25°C), pH, Redox Potential (Eh), Temperature (°C), Free gas at wellhead (CH₄)	Every six months until five
	Laboratory analytes	Major cations and anions: Calcium (Ca ²⁺), Magnesium (Mg ²⁺), Potassium (K ⁺), Sodium (Na ⁺), Bicarbonate (HCO ₃ ⁻), Carbonate (CO ₃ ⁻), Chloride (Cl ⁻), Sulphate (SO ₄ 2 ⁻), Total Alkalinity	samples obtained
		Metals (dissolved): Arsenic (As), Barium (Ba), Boron (B), Cadmium (Cd), Chromium (Cr), Cobalt (Co), Copper	
		(Cu), Iron (Fe), Lead (Pb), Manganese (Mn), Mercury (Hg), Nickel (Ni), Selenium (Se), Strontium (Sr ²⁺), Zinc (Zn)	_
		Fluoride (F ⁻), Total Dissolved Solids	_
		Gas (dissolved): Methane (CH ₄)	
Suite B	Laboratory	Isotopes: Strontium (87Sr/86Sr)	Once only
	analytes	Metals (dissolved): Strontium (Sr ²⁺)	in: SBK, HUT, PCP

Table 7: 2021 UWIR groundwater sampling parameters and frequency for groundwater monitoring points

4. Updated Impact Predictions

4.1 Groundwater drawdown extent

Following the approval of the Updated CSG WMMP on 22 November 2019, the 2019 UWIR for the Surat CMA was approved by the DES on 16 December 2019. On 17 March 2022, the 2021 UWIR for the Surat CMA was approved for release by the DES (this UWIR came into effect on 1 May 2022) and was the current UWIR at the time of writing this Report. The 2021 UWIR simulated an updated Arrow field development plan (FDP) compared to the 2019 UWIR.

Changes have occurred in the predicted groundwater drawdown extent across the different iterations of the UWIR regional groundwater model, resulting from the simulation of cumulative production from all operators FDP which have been revised over time.

At the time of reporting the 2021 UWIR model files had not yet been provided to Arrow in order to estimate the Arrow only predicted impacts. As such, a comparison of the 2019 UWIR long term cumulative predictive impacts to the UWIR 2021 long term cumulative predictive impacts has been undertaken in relation to Arrow's lease area.

The Springbok Sandstone 5m predicted drawdown extent is relatively the same as the 2019 UWIR (Figure 4-1), however there are some minor changes such as there being only one drawdown contour instead of the two in the 2019 UWIR. Similarly, the 2021 UWIR WCM 5 m predicted drawdown extent is relatively the same as the 2019 UWIR contours (Figure 4-2).

The Hutton Sandstone drawdown contour has decreased in the 2021 UWIR compared to the 2019 UWIR (Figure 4-3). The location of both predicted 5m drawdown contours are associated with the Horrane Fault; however, it should be noted that Arrow's investigation of the fault indicates that clay smearing in the fault zone limited hydraulic connectivity between the WCM and the Hutton



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 53 of 168


Sandstone (as per Section 4.4.5 of the 2021 UWIR). Nonetheless, the distribution of the 2021 UWIR Hutton Sandstone monitoring points is sufficiently spread across the predicted drawdown extent to detect any hydraulic connection.

The Precipice Sandstone drawdown contour has decreased in the 2021 UWIR compared to the 2019 UWIR (Figure 4-4). However, it is noted that the 2019 UWIR did not predict any Arrow-only drawdown greater than 5 m in the Precipice Sandstone.

The adequacy of the monitoring network to monitor Arrows predicted impacts is normally assessed based on the Arrow only predicted impact drawdown contours. However, based on the changes between the 2019 UWIR and 2021 UWIR cumulative predicted contours and that the monitoring network has not significantly changed since the last annual reporting, the monitoring network is considered adequate.

In regard to the Condamine Alluvium, section 6.5.2.5 of the 2021 UWIR notes the magnitude of impact is less than 0.3m for most of the area and the footprint of predicted impact is similar to that in the previous UWIR. The average net loss of water from the Condamine Alluvium to the WCM is predicted to be about 1,270 ML/year over the next 100 years. This is higher than predictions in the 2019 UWIR but comparable to predictions in the 2012 UWIR and 2016 UWIR.






ARROW ENERGY - SURAT GAS PROJECT

Figure 4-1: Updated CSG WMMP and 2019 and 2021 UWIR Combined Springbok Sandstone long-term affected area



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 55 of 168




ARROW ENERGY - SURAT GAS PROJECT

Figure 4-2: Updated CSG WMMP and 2019 and 2021 UWIR Combined WCM long-term affected area



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 56 of 168




ARROW ENERGY - SURAT GAS PROJECT

Figure 4-3: Updated CSG WMMP and 2019 and 2021 UWIR Combined Hutton Sandstone long-term affected area



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 57 of 168



ARROW ENERGY - SURAT GAS PROJECT

Figure 4-4: Updated CSG WMMP and 2019 and 2021 UWIR Combined Precipice Sandstone long-term affected area



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 58 of 168

5. WMMP Revision

In accordance with Section 8.6 of the SGP Updated WMMP, assessments are required to be undertaken upon the release of a new UWIR and after receiving technical files for that UWIR. These assessments are:

- revision of the Early Warning Monitoring System (EWMS);
- risk assessment of potential terrestrial groundwater dependent ecosystems (TGDE); and
- potential changes to stream connectivity.

The 2021 UWIR took effect on 1 May 2022. Technical files for the UWIR were partly received on 6 October 2022 related to the TGDE, and 10 May 2023 related to the EWMS. The desktop risk assessment of potential TGDEs has been completed on 21 December 2022 and review of the EWMS on 21 July 2023 (within 90 days of receiving the technical files as per the Updated WMMP).

The other assessment noted above (stream connectivity) is currently unable to be undertaken given their technical files have not yet been received. As noted in Section 4, there is minimal change to predicted drawdown between the 2019 and 2021 UWIR, therefore is unlikely that there would be significant change to the stream connectivity assessment.

An update on the EWMS and field assessment of potential TGDEs is provided in the following sections.

5.1 Early Warning Monitoring System (EWMS)

The EWMS has been updated following receipt of the technical files from OGIA. Revised EWMS values are presented in Table 8. The 2021 UWIR groundwater model was used to derive reduced EWMS levels for the Condamine Alluvium, Hutton Sandstone and Precipice Sandstone using the framework outlined in Section 7.5.2 of the SGP Updated WMMP. The EWMS levels for the Springbok Sandstone were not amended as the 2021 UWIR model predicts greater maximum cumulative drawdown in this formation, therefor maintaining the existing EWMS levels is a conservative approach for monitoring potential impacts of CSG related impacts.

Aquifer	Early Warning Indicator (EWI) (Commencing Jan 2022 to Dec 2024)	Trigger threshold (Commencing Jan 2022 to Dec 2024)	Limit
Condamine Alluvium	3.73m	5.59m	7.46m
Springbok Sandstone	31.2m	54.1m	77m
Hutton Sandstone	32.16m	48.23m	64.31m
Precipice Sandstone	3.11m	4.66m	6.21m

Table 8: Revised Early Warning Monitoring System (EWMS)



The reasons for this variance between the original and revised EWMS levels are predominantly due to model structure and parameter changes between the 2012 UWIR (the 2012 model was used in the SGP Updated WMMP because this model included uncertainty analysis from 200 realisations), the 2019 UWIR and the 2021 UWIR groundwater models, as well as changes in the development profile of CSG operations. An overview of these changes are provided in Section 6.4 of the 2021 UWIR.

Even with these reduced EWMS levels, there were no exceedances of early warning indicators, trigger thresholds or limits during the reporting period.

5.2 Field assessment of potential TGDEs

Section 5.2 of the WMMP Annual Report for the 2020-21 period outlined the results of the TGDE desktop assessment completed based on the 2019 UWIR. The assessment identified two sites (Juandah Creek and Wilkie Creek) which required field assessments to confirm they are TGDEs to be completed by 30 June 2022 and a summary report/s prepared within 90 days thereafter. This summary report is provided in Appendix D with key information provided here.

Ecological and hydrogeological field surveys of Juandah Creek and Wilkie Creek were completed on 13 October 2021 and 15 October 2021 respectively.

Juandah Creek

The assessment of the Juandah Creek site identified that Quaternary alluvial deposits of primarily sand with some clay extend along the Juandah Creek potential TGDE area. Juandah creek traverses and shallowly incises the regionally south-westerly dipping Great Artesian Basin (GAB) sequence, including the WCM at the far northern end of the area, Springbok Sandstone in the central to northern section of the area and Westbourne Formation at the southernmost end of the area.

Most lines of evidence supported that the deeper-rooted trees assessed were utilising relatively fresh and isotopically enriched groundwater from the basal alluvium, likely recharged primarily from rainfall directly infiltrating the alluvium in addition to surface water run off / stream flow. One of the three conceptual models developed as part of the assessment identified the potential for vertical upward leakage, namely:

- Dry season with vertical upward leakage: where upward leakage of bedrock aquifers is occurring into the base of the alluvium in the dry season, which is acting to support floodplain vegetation where other sources of moisture have been depleted. The capacity of this leakage to stimulate vegetation growth and vigour is dependent to a degree on the groundwater salinity of the leaking aquifers. It is not possible to predict the extent to which this is occurring without more detailed assessment during a drier climatic period. It is however conceptualised to be restricted to discrete areas and pockets where the function is supported by underlying geology, rather than occurring more extensively across the landscape.

The conceptual model will be subjected to further testing through additional assessment during a prolonged dry period to address abovementioned critical research gaps and subsequent refinement of the eco-hydrogeological conceptual model. Attempts were made to visit reaches of Juandah Creek in the dry season



of 2023 to collect additional data for testing the conceptual model, however, land access was not granted.

While the collected data indicate that the site is not a TGDE reliant on the regional aquifer hosted within the GAB, an EWMS (Early Warning Management System) has been developed for the site as per the required timelines in the updated WMMP which dated back to 29 December 2022. EWMS trigger levels were plotted along with EWMS monitoring bores hydrographs (refer to Appendix A), illustrating that EWMS monitoring bores groundwater levels are higher than EWMS trigger levels confirming that the risk to TGDE is low.

Wilkie Creek

Prior to commencement of significant identified hydrological and hydrogeological alteration which commenced in 1990, it is considered likely that vegetation within portions of the identified reach of Wilkie Creek and an extension downstream to the north was dependent, at least seasonally, on groundwater. This is consistent with the classification of river red gum as a facultative phreatophyte.

However severe degradation of the ecosystem including widespread mature tree dieback, likely due to exposure to shallow saline groundwater, has resulted in ecosystem collapse. In the current hydrogeological regime, no trees within the affected reach were identified as being groundwater reliant. Elevated groundwater salinity is considered the major factor contributing to the poor ecological health of the reach of Wilkie Creek that is subject to this assessment. The riparian vegetation is still relatively intact immediately north of Dalby-Kogan Road where the preferential source of water appeared to be shallow soil moisture at the time of assessment.

The conceptual model identifies numerous potential stressors to the riparian ecosystem on Wilkie Creek which appear to have commenced from 1990 and are likely a result of activities other than Arrow's operations.. Further investigations will be conducted to address the impact of potential stressors to the riparian ecosystem of Wilkie Creek and subsequently refine the eco-hydrogeological conceptual model. Similar to Juandah Creek, attempts were made to visit reaches of Wilkie Creek in the dry season of 2023 to collect additional data for testing the conceptual model, however, land access was not granted. Arrow will continue efforts to visit both of the abovementioned creeks.

5.3 Potential terrestrial groundwater dependent ecosystems

The 2019 UWIR included an assessment of terrestrial groundwater dependent ecosystems (GDE) which was further revised in OGIA's 2019 UWIR Approval Condition 3 Response (OGIA, 2020) released on 16 December 2020. This document was submitted to the DES by OGIA as part of the conditions of approval of the 2019 UWIR¹. The document is available from OGIA upon request. The 2021 UWIR also included an assessment of terrestrial GDEs which required a follow up desktop assessment to be conducted by Arrow. The associated technical data were provided to Arrow on 6 October 2022 in response

¹ The Chief Executive of the Department of Environment and Science approved the 2019 Surat CMA UWIR on 16 December 2019 with conditions including Condition 3 which required submission of an environmental values assessment with the first annual review that updates the assessment of impacts presented in the approved UWIR on the following environment values: a. terrestrial groundwater dependent ecosystems; b. changes in water quality of each aquifer; and c. irrigation land.



to Arrow's request in June 2022 following the SGP commencement on 22 October 2020 and the 2021 UWIR taking effect on 1 May 2022.

Arrow was obliged to revise the terrestrial GDE risk assessment in accordance with Section 8.6 of the SGP Updated WMMP. Arrow completed the revised desktop risk assessment on 21 December 2022 (within 90 days from 6 October 2022) i.e. within 90 days of a new approved UWIR being issued (and upon receiving technical files from OGIA). Arrow's revised risk assessment is provided in Appendix D.

The risk assessment identified eight potential terrestrial GDEs predicted to be at risk of being impacted from the Action or the cumulative CSG operation. A summary of the desktop risk assessment is provided below, with further detail provided in Appendix D. As a result, further work is required to be undertaken to gather supporting data to confirm the ecosystems' reliance on groundwater and validate the findings of the desktop assessment. The risk assessment for terrestrial GDEs was included as a revision to the Updated WMMP in the form of an addendum, which was submitted to DCCEEW on 15 March 2023. The proposed approach was confirmed by DCCEEW on 5 April 2023 to be in accordance with commitments in Section 5.4.3 of the active Update CSG WMMP. Arrow is conducting the further work in compliance with the addendum.

Risk assessment

OGIA's terrestrial GDE desktop assessment method (OGIA, 2020), detailed in the document Attachment 1 Condition 3 Response, integrates:

- GIS mapping of potential terrestrial GDEs
- areas of predicted drawdown in the 2019 UWIR groundwater model within outcropping aquifers
- regional ecosystem (RE) mapping
- biodiversity status.

Twelve potential terrestrial GDE areas were identified by OGIA on Arrow tenure as potentially at risk of impact. Arrow assessed these twelve sites against available data such as depth to groundwater, landscape setting, field survey vegetation mapping, and previous assessments conducted in the Stage 1 CSG WMMP and Revision 0 of the Updated CSG WMMP (Appendix D – Stream Connectivity and GDE Impact Assessment memo). Arrow's review identified that eight of the twelve areas are considered to be at risk of impact or likely to represent a terrestrial GDE.

OGIA (2020) note that the priority knowledge gaps for further investigation of medium or high-risk sites are:

- validation and confirmation of the GDE mapping and associated REs
- conceptualisation of the identified terrestrial GDEs in terms of:

- quantification of their ecological water requirements – the temporal nature, quantity and quality of groundwater use

- their likely ecological response to changes in groundwater regime.



6. Compliance with the WMMP

The approved SGP Updated WMMP was developed based on an adaptive management framework which meets the water-related approval conditions. Compliance, therefore, with the SGP Updated WMMP demonstrates compliance with the approval conditions.

Throughout the reporting period, Arrow maintained compliance with the WMMP with the exception of twelve bores which had periods with no groundwater level/pressure monitoring (Section 3.1). Compliance with the WMMP is demonstrated through:

- publication of the approved Updated CSG WMMP on Arrow's website
- publication of this annual report on Arrow's website within three months of the anniversary of the start of the SGP
- providing raw data to OGIA as required in Section 9.13 of the 2021 UWIR for potential inclusion (at the discretion of Department of Regional Development, Manufacturing and Water [DRDMW]) on the Queensland Globe database
- met performance measure criteria for assessment of the protection of matters of national environmental significance (MNES), namely:
 - adequacy of the groundwater monitoring network was reviewed according to the predicted drawdown from a new OGIA model (2021 UWIR) (Section 4.1)
 - the desktop terrestrial GDE risk assessment was reviewed following the release of a new UWIR (2021 UWIR) (Section 5.3)
 - monitoring obligations (groundwater and subsidence) were carried out in accordance with the 2021 UWIR with the exception of Plainview 16, Tipton-197, Carn Brea-18, Carn Brea-19, Carn Brea-20, Plainview 34, Castledean-18, Daandine-164, Tipton 196A, Tipton 200, Tipton-194 and Kedron-570 which had periods with no groundwater level/pressure monitoring (Section 3.1)
- the EWMS was implemented noting that there were no exceedances of early warning indicators, trigger thresholds or limits during the reporting period.

In addition to the above, Arrow's compliance with all EPBC Approval 2010/5344 conditions is documented in the report Surat – EPBC Approval 2010/5344 Annual Compliance Report 2022/2023 (S00-ARW-ENV-REP-00064) available on Arrow's website.





S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 64 of 168

7. Document Administration

This document has been created using ORG-ARW-IMT-TEM-00005 v4.0

Revision	Revision Date	Revision Summary	Author
1	19/01/2024	Issued for Use	Yousef Beiraghdar
Related do	ocuments		
Document Nu	umber	Document title	
	e and release		
Author Position		Incumbent	Release Date
Team Lead H	lydrogeology	Yousef Beiraghdar	19/01/2024
	ly alogoology		
Stakaholde	ers and reviewe	rs	
Stakenolud			
Position		Incumbent	Review Date
			Review Date 19/01/2024
Position	Subsidence	Incumbent	
Position Team Lead S	Subsidence geologist	Incumbent Kane Eskola	19/01/2024
Position Team Lead S Senior Hydro	Subsidence geologist	Incumbent Kane Eskola Andrew Wilson	19/01/2024 19/01/2024
Position Team Lead S Senior Hydro	Subsidence geologist Manager	Incumbent Kane Eskola Andrew Wilson	19/01/2024 19/01/2024
Position Team Lead S Senior Hydro Groundwater	Subsidence geologist Manager	Incumbent Kane Eskola Andrew Wilson	19/01/2024 19/01/2024





S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 66 of 168

8. References

Aghighi, H, Schöning, G, Cui, T, Pandey, S, (2023). *Exploring the contribution of coal shrinkage to coal seam gas induced subsidence: a research update paper by the Office of Groundwater Impact Assessment (OGIA)*, Department of Regional Development, Manufacturing and Water, Queensland Government, April 2023.

Department of Natural Resources, Mines and Energy, 2017. *Identification of Gaining Streams in the Surat Cumulative Management Area, Hydrogeology Investigation Report*, March 2017, Office of Groundwater Impact Assessment

DES, 2023. Guideline Environmental Protection (Water and Wetland Biodiversity) Policy 2019 Deciding aquatic ecosystem indicators and local water quality guideline values. Department of Environment and Science (DES), Queensland Government, October 2023.

DES, 2021. Using monitoring data to assess groundwater quality and potential environmental impacts, Version 2. Department of Environment and Science (DES), Queensland Government, March 2017.

Office of Groundwater Impact Assessment, 2019. Underground Water Impact Report for the Surat Cumulative Management Area, July 2019. Queensland Government

Office of Groundwater Impact Assessment, 2019b. *Groundwater Modelling Report – Surat Cumulative Management Area*, Queensland Government, October 2019


Office of Groundwater Impact Assessment, 2021. Underground Water Impact Report 2021 for the Surat Cumulative Management Area, Queensland Government, December 2021


Office of Groundwater Impact Assessment, 2021b. *Details of the Water Monitoring Strategy for the Underground Water Impact Report 2021*. Queensland Government, December 2021



Appendix A – Groundwater Level Monitoring Bores Hydrographs











S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 69 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 70 of 168








S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 71 of 168







energy


go further

S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 72 of 168






















S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 75 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 76 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 77 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 78 of 168















S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 80 of 168


























Castledean-18 - Taroom CM (CA18_WCMc_1p) 310 305 * ٠ 300 **Croundwater Elevation** (MHD) 290 280 280 \$ 4 4 Logger data \$ ٠ 4 1 275 ٥ 270 265













S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 85 of 168
















S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 87 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 88 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 89 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 90 of 168










S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 91 of 168

















S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 93 of 168

































S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 97 of 168
























S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 100 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 101 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 102 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 103 of 168










S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 104 of 168























S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 107 of 168













S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 109 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 110 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 111 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 112 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 113 of 168



























S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 117 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 118 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 119 of 168














S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 121 of 168














S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 123 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 124 of 168










S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 125 of 168
















S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 127 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 128 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 129 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 130 of 168














S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 132 of 168










S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 133 of 168















S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 135 of 168










S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 136 of 168
















S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 138 of 168










S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 139 of 168
















S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 141 of 168








S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 142 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 143 of 168


Early Warning Management System Hydrographs









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 144 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 145 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 146 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 147 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 148 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 149 of 168









S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 150 of 168








S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 151 of 168







S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 152 of 168

Appendix B – Groundwater quality results



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 153 of 168

Report

	Wat	er quality guide	lines	1		Plainview 36					Stratheden-63					All bores		
Parameter	Stock water	Drinking water (ADWG)	Aquatic (ANZG 95%)	Count	Count below LOR	20th	50th	80th	Count	Count below LOR	20th	50th	80th	Count	Count below LOR	20th	50th	80th
87Sr/86Sr		(ADWG)	3378)	5	0	0.704073	0.70409	0.704097	1	0	0.70481	0.70481	0.70481	5	0	0.704072	0.704091	0.704258
Arsenic - Dissolved	0.5	0.01	0.013	6	6	0.001	0.001	0.001	9	9	0.001	0.001	0.001	13	13	0.001	0.001	0.001
Barium - Dissolved		2		6	0	0.127	0.131	0.137	9	0	0.4618	0.54	0.6234	13	0	0.1458	0.475	0.6054
Bicarbonate Alkalinity as CaCO3			165-283- 677	6	0	411	424	448	9	1	15	46	64	15	1	31.6	66	422.8
Boron - Dissolved	5	4	0.94	6	0	0.15	0.16	0.17	9	0	0.1	0.13	0.184	13	0	0.108	0.16	0.18
Cadmium - Dissolved	0.01	0.002	0.0002	6	6	0.0001	0.0001	0.0001	9	9	0.0001	0.0001	0.0001	13	13	0.0001	0.0001	0.0001
Calcium - Dissolved			2-20-86	6	0	10	10.5	12	9	0	42	66	119	15	0	10.8	40	78.6
Carbonate Alkalinity as CaCO3				6	1	22	25.5	28	9	4	1	5	13.2	15	5	1	12	27.2
Chloride		5	186-737- 2939	6	0	185	194	199	9	0	1,072	1,170	1,420	15	0	194	1,030	1,284
Chromium - Dissolved	1	0.05	0.001	6	6	0.001	0.001	0.001	9	9	0.001	0.001	0.001	13	13	0.001	0.001	0.001
Cobalt - Dissolved	1			6	6	0.001	0.001	0.001	9	9	0.001	0.001	0.001	13	13	0.001	0.001	0.001
Copper - Dissolved	0.4 to 5	1	0.0014	6	3	0.001	0.001	0.001	9	9	0.001	0.001	0.001	13	11	0.001	0.001	0.001
Fluoride	2	1.5		6	0	0.2	0.3	0.3	9	0	0.2	0.2	0.24	15	0	0.2	0.2	0.3
Iron - Dissolved		0.3		6	3	0.05	0.06	0.15	9	9	0.05	0.05	0.05	13	10	0.05	0.05	0.062
Lead - Dissolved	0.1	0.01	0.0034	6	6	0.001	0.001	0.001	9	9	0.001	0.001	0.001	13	13	0.001	0.001	0.001
Magnesium - Dissolved			2-8-82	6	0	4	4	4	9	1	7	9	12	15	1	4	6	11
Manganese - Dissolved		0.1	1.9	6	0	0.051	0.058	0.066	9	1	0.002	0.005	0.0094	13	1	0.0024	0.007	0.0552
Mercury - Dissolved	0.002	0.001	0.0006	6	6	1.00E-04	1.00E-04	1.00E-04	9	9	1.00E-04	1.00E-04	1.00E-04	13	13	1.00E-04	1.00E-04	1.00E-04
Methane				6	0	2090	2630	3530	8	0	8538	11600	16800	12	0	2498	8600	13260
Nickel - Dissolved	1	0.02	0.011	6	1	0.002	0.0025	0.005	9	6	0.001	0.001	0.0014	13	6	0.001	0.001	0.0026
Potassium - Dissolved				6	0	4	4	4	9	0	5	6	7	15	0	4	5	7
Selenium - Dissolved	0.02	0.01	0.011	6	6	0.01	0.01	0.01	9	9	0.01	0.01	0.01	13	13	0.01	0.01	0.01
Sodium - Dissolved		180	246-677- 1821	6	0	294	298.5	316	9	0	669	712	729	15	0	299.4	653	722.6
Strontium - Dissolved				6	0	0.365	0.3705	0.405	9	0	1.37	1.79	2.83	13	0	0.4222	1.37	2.402
Sulfate as SO4 - Turbidimetric - Dissolved		250	1-8-47	6	5	1	1	1	9	0	10	21	27	15	5	1	9	22.8
Total Alkalinity as CaCO3			195-309- 790	6	0	435	446	454	9	0	18	62	77	15	0	41.2	78	444.8
Total Dissolved Solids @180°C	2000 to 5000	600		6	0	727	754	801	9	0	1968	2210	2692	13	0	803.4	1980	2496
Zinc - Dissolved	20	3	0.008	6	0	0.019	0.033	0.08	9	9	0.005	0.005	0.005	13	9	0.005	0.005	0.0202

Note the ADWG adopted is generally for health, in instances where aesthetic or recreational values are lower, these are shown. Irrigation values show a range in some instances representing the long-term and short-term criteria. Where there are multiple values in the aquatic ecosystem column, this represents the 20th percentile – 50th percentile-80th percentile values.

S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 154 of 168



Original Chemical Name	Sample_Id	analysis_date	qualifier	result_value	result_unit	detection_limit	technical_reference
FIELD DISS OX	Plainview 36 19/11/2022 12:41:18_F	19/11/2022 12:41		0.419999987	%		Field Measurement
FIELD EC	Plainview 36 19/11/2022 12:41:18_F	19/11/2022 12:41		1340	us/cm		Field Measurement
FIELD pH	Plainview 36 19/11/2022 12:41:18 F	19/11/2022 12:41		7.96999979			Field Measurement
FIELD REDOX	Plainview 36 19/11/2022 12:41:18 F	19/11/2022 12:41		-118.5	mv		Field Measurement
FIELD TEMP	Plainview 36 19/11/2022 12:41:18 F	19/11/2022 12:41		22,20000076	degree		Field Measurement
87Sr/86Sr	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		0.704083025		0.01	Sr_ISOTOPE: Ratio of 87Sr and 86Sr analysis
Arsenic - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	0.001	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Barium - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		0.133000001	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Bicarbonate Alkalinity as CaCO3	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		461	mg/L	1	ED037-P: Alkalinity by Auto Titrator
Boron - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		0.180000007	mg/L	0.05	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Butane	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	10	μg/L	10	EP033: C1 - C4 Gases
Butene	Plainview 36 17/11/2022 10:00:00	7/12/2022 6:16	<	10	μg/L	10	EP033: C1 - C4 Gases
Cadmium - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	16 1E-04	mg/L	0.0001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Calcium - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	`	12	mg/L	1	ED093F: Major Cations - Dissolved
Carbonate Alkalinity as CaCO3	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		27	mg/L	1	ED037-P: Alkalinity by Auto Titrator
Chloride	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		202	- V	1	ED037-P. Alkalinity by Add Titratol ED045G: Chloride by Discrete Analyser
			-	0.001	mg/L	0.001	
Chromium - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	0.001	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Cobalt - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<		mg/L		EG020A-F: Dissolved Metals by ICP-MS - Suite A
Copper - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	+	0.001	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Ethane	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	10	μg/L	10	EP033: C1 - C4 Gases
Ethene	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	10	μg/L	10	EP033: C1 - C4 Gases
Fluoride	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		0.20000003	mg/L	0.1	EK040P: Fluoride by Auto Titrator
Hydroxide Alkalinity as CaCO3	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	1	mg/L	1	ED037-P: Alkalinity by Auto Titrator
Ionic Balance	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		0.209999993	%	0.01	EN055 - PG: Ionic Balance by PCT DA and Turbi SO4 DA
Iron - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		0.07	mg/L	0.05	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Lead - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	0.001	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Magnesium - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		4	mg/L	1	ED093F: Major Cations - Dissolved
Manganese - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		0.057999998	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Mercury - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	1E-04	mg/L	0.0001	EG035F: Dissolved Mercury by FIMS
Methane	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		2090	μg/L	10	EP033: C1 - C4 Gases
Nickel - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		0.002	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Potassium - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		4	mg/L	1	ED093F: Major Cations - Dissolved
Propane	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	10	μg/L	10	EP033: C1 - C4 Gases
Propene	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	10	μg/L	10	EP033: C1 - C4 Gases
Selenium - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	0.01	mg/L	0.01	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Sodium - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		330	mg/L	1	ED093F: Major Cations - Dissolved
Strontium - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		0.405000001	mg/L	0.001	EG020B-F: Dissolved Metals by ICP-MS - Suite B
Sulfate as SO4 - Turbidimetric - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	<	1	mg/L	1	ED041G: Sulfate (Turbidimetric) as SO4 2- by Discrete Analyser
Total Alkalinity as CaCO3	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16	-	488	mg/L	1	ED037-P: Alkalinity by Auto Titrator
Total Anions	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		15.39999962	meq/L	0.01	EN055 - PG: Ionic Balance by PCT DA and Turbi SO4 DA
Total Cations	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		15.39999962	meq/L	0.01	EN055 - PG: Ionic Balance by PCT DA and Turbi SO4 DA
Total Dissolved Solids @180°C	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		801	mg/L	10	EA015H: Total Dissolved Solids (High Level)
Zinc - Dissolved	Plainview 36 17/11/2022 18:00:00	7/12/2022 6:16		0.018999999	mg/L	0.005	EG020A-F: Dissolved Metals by ICP-MS - Suite A
FIELD DISS OX	Plainview 36 29/04/2023 11:09:33 F	29/04/2023 11:09		0.330000013	%	0.003	Field Measurement
FIELD EC	Plainview 36 29/04/2023 11:09:33 F	29/04/2023 11:09		1719	us/cm		Field Measurement
FIELD EC	Plainview 36 29/04/2023 11:09:33 F	29/04/2023 11:09		8.239999771	us/cm		Field Measurement
FIELD REDOX				-142.6000061			
	Plainview 36 29/04/2023 11:09:33_F	29/04/2023 11:09			mv		Field Measurement
FIELD TEMP	Plainview 36 29/04/2023 11:09:33_F	29/04/2023 11:09		24.89999962	degree	0.001	Field Measurement
Arsenic - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	0.001	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Barium - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	_	0.165000007	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Bicarbonate Alkalinity as CaCO3	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	_	411	mg/L	1	ED037-P: Alkalinity by Auto Titrator
Boron - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		0.17000002	mg/L	0.05	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Butane	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	10	μg/L	10	EP033: C1 - C4 Gases
Butene	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	10	μg/L	10	EP033: C1 - C4 Gases
Cadmium - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	1E-04	mg/L	0.0001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Calcium - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		12	mg/L	1	ED093F: Major Cations - Dissolved
Carbonate Alkalinity as CaCO3	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		24	mg/L	1	ED037-P: Alkalinity by Auto Titrator
Chloride	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		192	mg/L	1	ED045G: Chloride by Discrete Analyser
	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	0.001	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Chromium - Dissolved	FIAILIVIEW 30 23/04/2023 11:00:00						

S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 155 of 168



Copper - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		0.002	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Ethane	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	10	μg/L	10	EP033: C1 - C4 Gases
Ethene	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	10	μg/L	10	EP033: C1 - C4 Gases
Fluoride	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		0.300000012	mg/L	0.1	EK040P: Fluoride by Auto Titrator
Hydroxide Alkalinity as CaCO3	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	1	mg/L	1	ED037-P: Alkalinity by Auto Titrator
Ionic Balance	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		0.560000002	%	0.01	EN055 - PG: Ionic Balance by PCT DA and Turbi SO4 DA
Iron - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		0.150000006	mg/L	0.05	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Lead - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	0.001	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Magnesium - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		4	mg/L	1	ED093F: Major Cations - Dissolved
Manganese - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		0.050999999	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Mercury - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	1E-04	mg/L	0.0001	EG035F: Dissolved Mercury by FIMS
Methane	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		3530	μg/L	10	EP033: C1 - C4 Gases
Nickel - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		0.002	mg/L	0.001	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Potassium - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		4	mg/L	1	ED093F: Major Cations - Dissolved
Propane	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	10	μg/L	10	EP033: C1 - C4 Gases
Propene	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	10	μg/L	10	EP033: C1 - C4 Gases
Selenium - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	0.01	mg/L	0.01	EG020A-F: Dissolved Metals by ICP-MS - Suite A
Sodium - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		297	mg/L	1	ED093F: Major Cations - Dissolved
Strontium - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		0.448000014	mg/L	0.001	EG020B-F: Dissolved Metals by ICP-MS - Suite B
Sulfate as SO4 - Turbidimetric - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50	<	1	mg/L	1	ED041G: Sulfate (Turbidimetric) as SO4 2- by Discrete Analyser
Total Alkalinity as CaCO3	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		435	mg/L	1	ED037-P: Alkalinity by Auto Titrator
Total Anions	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		14.10000038	meq/L	0.01	EN055 - PG: Ionic Balance by PCT DA and Turbi SO4 DA
Total Cations	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		13.89999962	meq/L	0.01	EN055 - PG: Ionic Balance by PCT DA and Turbi SO4 DA
Total Dissolved Solids @180°C	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		807	mg/L	10	EA015H: Total Dissolved Solids (High Level)
Zinc - Dissolved	Plainview 36 29/04/2023 11:00:00	9/05/2023 5:50		0.021	mg/L	0.005	EG020A-F: Dissolved Metals by ICP-MS - Suite A
87Sr/86Sr	Plainview 36 29/04/2023 11:00:00	25/05/2023 7:25		0.704091012		0.01	Sr_ISOTOPE: Ratio of 87Sr and 86Sr analysis

S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 156 of 168



Report

Appendix C – Mann-Kendall Summary



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 157 of 168

Monitoring Unit	Field	Bore Name	Mann-Kendall Trend	Analyte	No. of data points	Mann-Kendall Statistic (S)
Springbok Sandstone	Plainview	Plainview 36	More data needed	FIELD DISS OX	6	-5
Springbok Sandstone	Plainview	Plainview 36	Increasing	FIELD EC	6	13
Springbok Sandstone	Plainview	Plainview 36	Stable	FIELD PH	6	-8
Springbok Sandstone	Plainview	Plainview 36	Stable	FIELD REDOX	6	-7
Springbok Sandstone	Plainview	Plainview 36	Stable	FIELD TEMP	6	-3
Springbok Sandstone	Plainview	Plainview 36	Increasing	Calcium	6	13
Springbok Sandstone	Plainview	Plainview 36	Stable	Magnesium	6	0
Springbok Sandstone	Plainview	Plainview 36	Increasing	Sodium	6	9
Springbok Sandstone	Plainview	Plainview 36	Stable	Potassium	6	-3
Springbok Sandstone	Plainview	Plainview 36	Increasing	Chloride	6	9
Springbok Sandstone	Plainview	Plainview 36	Stable	Carbonate Alkalinity	6	-1
Springbok Sandstone	Plainview	Plainview 36	More data needed	Bicarbonate Alkalinity	6	3
Springbok Sandstone	Plainview	Plainview 36	More data needed	Total Alkalinity	6	5
Springbok Sandstone	Plainview	Plainview 36	Stable	Sulfate	6	0
Springbok Sandstone	Plainview	Plainview 36	Stable	Fluoride	6	-4
Springbok Sandstone	Plainview	Plainview 36	More data needed	Dissolved Barium	6	7
Springbok Sandstone	Plainview	Plainview 36	Increasing	Dissolved Strontium	6	15

Note this only shows results with 4 or more data points



Appendix D – Field assessment of potential TGDEs related to the SGP WMMP using the 2019 UWIR



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 159 of 168

FILE NOTE



FROM:	Arrow Energy	REF:	
SUBJECT:	Summary of field verification of Wilkie Creek and Juandah C dependent ecosystems sites as identified in Updated WMMF		

The purpose of this File Note is to provide a summary of the field assessment undertaken at the two sites identified as potential terrestrial groundwater dependent ecosystems (TGDE) potentially at impact from the Action.

- 1. Juandah Creek, is located 10 km southeast of Wandoan on PL494 and the potential TGDE is predominantly associated with riparian vegetation flanking a defined reach of Juandah Creek.
- 2. Wilkie Creek is located 28 km northwest of Dalby on PL194 and PL230 and the potential TGDE is predominantly associated with riparian vegetation flanking

These two sites were identified through the desktop assessment undertaken by Arrow Energy based on the 2019 Underground Water Impact Report (UWIR) and documented in the File Note presented in the 2022 Updated Water Monitoring and Management Plan (WMMP) Annual Report (available at arrowenergy.com.au).

Juandah Creek

An ecological and hydrogeological field survey of the Wilkie Creek mapped TGDE was undertaken over a 2day period (11 – 13th October 2021). The assessment coincided with a rainfall event in the region with 35.2mm falling at Miles (60km to the south) on the 12th and 13th October, although no rainfall was received at the study site. In total, four targeted sites were assessed during the field assessment.

Field assessment methods

Assessment of the Juandah Creek site comprised a desktop assessment followed by a field assessment which included:

- Descriptions of creek hydrology, geomorphology and ecology;
- Measurements of Leaf Area Index (LAI) using an automated canopy imaging camera (C110 Plant Canopy Imager);
- Pre-dawn leaf water potential (LWP) measurements from mature Forest Red Gum (Eucalyptus tereticornis) using a Scholander LWP Meter;
- Surface water sample collection for measurement of field water quality parameters and laboratory analysis of a standard water quality suite and ²²²radon;
- Advancement of hand auger holes within alluvium within and on the levees of Juandah Creek using an AMS hand auger, aiming to intersect the groundwater table, or until indurated sedimentary basement rock was intersected;
- Description of the geological profile encountered;
- Collection of groundwater samples from hand auger bores for measurement of field water quality parameters; and

• Collection and analysis of soil, leaf water, surface water and groundwater from hand augers for analysis of stable isotopes of oxygen and deuterium.

Eco-hydrogeological conceptual site model

The reach of Juandah Creek mapped as a potential TGDE has been categorised as a mid-catchment alluvial system. Quaternary alluvial deposits of primarily sand with some clay extend along the Juandah Creek study area, with maximum cross-sectional width of 500 metres and anticipated maximum depths of less than 15 metres, but generally <5m.

Juandah creek traverses and shallowly incises the regionally south-westerly dipping Great Artesian Basin (GAB) sequence, including the Walloon Coal Measures (WCM) at the far northern end of the mapped TDGE, Springbok Sandstone in the central to northern section of the TGDE and Westbourne Formation at the southernmost end of the TDGE.

Available data indicates the basal alluvial system forms a predominantly continuously saturated system (below ground level), likely recharged primarily from rainfall directly infiltrating the alluvium in addition to surface water run off / stream flow.

Regional groundwater pressure monitoring in the upper WCM members (Macalister) across the northern half of the mapped TGDE show that the groundwater pressures are near-surface, respond positively to rainfall recharge events and are therefore likely to locally comprise recharge intake beds during periods of prolonged and above-average rainfall. It is possible that during low rainfall, drying periods, relatively high pressures within the upper WCM may provide an ongoing source of moisture to the alluvium and deeper-rooted vegetation that may extend to the basal alluvium and into the upper WCM. Further assessment during a prolonged dry period would be required to fully test this hypothesis. It however cannot be discounted given heavy rainfall in the months prior to the assessment, which could have resulted in dilution of the geochemical signature of bedrock aquifers at the base of the alluvium.

Shallow groundwater levels of <10 mbGL in the WCM across the northern half of the mapped TDGE (if present) would, in theory, provide a direct water source for vegetation where the WCM sequence outcrops or the shallow alluvium is unsaturated. The salinity of any groundwater leakage into the rooting zone of riparian vegetation may however limit its capacity to stimulate vegetative growth or productivity.

Three eco-hydrogeological conceptualisations of the Juandah Creek site were developed based on the available data and are summarised here:

- 1. Dry season: this conceptualisation indicates a dry season scenario whereby groundwater perched in the channel sands is being utilised by riparian vegetation along the margins of the drainage. In this scenario, while the potentiometric surface of the bedrock aquifers intrudes into (or above) the base level of the alluvium, there is no leakage due to the tightness of the sandstone bedrock and lack of fracturing. Perched groundwater in the alluvium and GAB aquifers are vertically isolated by a low permeability GAB regolith interburden, and do not mix. Vegetation moisture sources are being supplied by the perched aquifer and soil moisture alone.
- 2. Dry season with vertical upward leakage: Provides a variation on the dry season conceptualisation, where upward leakage of bedrock aquifers is occurring into the base of the alluvium in the dry season, which is acting to support floodplain vegetation where other sources of moisture have been depleted. The capacity of this leakage to stimulate vegetation growth and vigour is dependent to a degree on the groundwater salinity of the leaking aquifers. It is not possible to predict the

extent to which this is occurring without more detailed assessment during a drier climatic period. It is however conceptualised to be restricted to discrete areas and pockets where the function is supported by underlying geology, rather than occurring more extensively across the landscape.

3. Post-flooding / Wet season: a post-flooding / wet season conceptualisation where the perched aquifer at the base of the Juandah Creek floodplain alluvium has been replenished by seasonal rainfall and / or overbank flow. Any leakage of GAB aquifers into the base of the alluvium would be diluted by the perched groundwater table, making it difficult to differentiate based on groundwater geochemistry.

Any response of riparian vegetation to CSG extraction would be variable and difficult to predict, depending on a number of factors including:

- The extent of bedrock aquifer leakage into the alluvium, including leakage volumes and wetted area;
- Salinity of GAB aquifer leakage; and
- Climatic factors including periods of extended drought and rainfall recharge.

River red gum, and its closely allied species forest red gum (Eucalyptus tereticornis which is the dominant species is the assessment area) is an adaptable species that is adapted to arid and semi-arid environments and will go through alternate phases of shedding and regaining its crown, depending on the availability of water. It is adapted to do so over time and across the flood frequency classes. River red gum have the capacity to self-regulate and adjust their transpiration rates to match the average flood return interval (Colloff 2014). The species is considered opportunistic in its water use, sourcing water according to osmotic and matric water potential and source reliability (Thorburn et al., 1993; Mensforth et al., 1994; Holland et al., 2006; Doody et al., 2009) with the water requirements obtained from three main sources being groundwater, rainfall, and river flooding. Doody et al. (2015) demonstrated that soil moisture alone can sustain the health of Eucalyptus camaldulensis through periods of drought for up to six years before significant decline in tree health is noted. With these ecological considerations, and based on the conceptualisations above, impacts on riparian vegetation are likely to be discrete and difficult to detect above current base levels of tree senescence caused by long-term drought alone.

Conclusions

It is considered highly likely that vegetation within the identified reach of Juandah Creek is dependent on groundwater within the shallow alluvium. The field assessment was undertaken during a relatively wet period and there was no information gathered during the survey that supported the hypothesis that trees were sourcing groundwater from deeper GAB aquifers at the time of the assessment. Most lines of evidence supported that the deeper-rooted trees assessed were utilising relatively fresh and isotopically enriched groundwater from the basal alluvium.

Hypotheses are provided for GDE water requirements as well as likely responses to changes in the groundwater regime through an assessment of water sources and pathways within an eco-hydrogeological conceptual site model. Such hypotheses need further testing through additional assessment during a prolonged dry period to address critical research gaps and subsequent refinement of the eco-hydrogeological conceptual model.

Wilkie Creek

An ecological and hydrogeological field survey of the Wilkie Creek mapped TGDE was undertaken over a 2.5-day period (13th, 14th and 15th October 2021). The assessment coincided with a rainfall event with 44 mm falling in Dalby on the 14th of October (prior to surface water quality sampling) which introduced some ambiguity into the results of water quality and geochemical sampling. Attempts were made throughout 2022 to return to the area for a follow up survey however the above average rainfall experienced throughout the year inhibited the ability to conduct a survey that would not be influenced by recent rainfall.

Field assessment methods

Assessment of the Wilkie Creek site comprised a desktop assessment followed by a field assessment which included:

- Descriptions of creek hydrology, geomorphology and ecology;
- Measurements of Leaf Area Index (LAI) using an automated canopy imaging camera (C110 Plant Canopy Imager);
- Pre-dawn leaf water potential measurements from mature River Red Gums using a Scholander Leaf Water Potential Meter;
- Surface water sample collection for measurement of field water quality parameters and laboratory analysis of a standard water quality suite and ²²²radon;
- Advancement of hand auger bores within alluvium on each side of the creek using an AMS hand auger to a depth below the groundwater table (if present), or until the indurated sedimentary basement rock was intersected;
- Description of the geological profile encountered;
- Collection of groundwater samples from hand auger bores for measurement of field water quality parameters and laboratory analysis of a standard water quality suite, ²²²radon; and
- Collection and analysis of soil, leaf water, surface water and groundwater from hand augers for analysis of stable isotopes of oxygen and deuterium.

Eco-hydrogeological conceptual site model

Lines of evidence drawn from data and observations from both the desktop and field assessments has culminated in the preparation of a preliminary eco-hydrogeological conceptual site model for the potential Wilkie Creek TGDE.

The reach of Wilkie Creek mapped as a potential TGDE forms the western margin of the Condamine River Alluvium (CRA) Quaternary alluvial deposits which thicken eastwards and northwards towards the Condamine River.

There is a strong association with the position and orientation of Wilkie Creek and the underlying geology. Notably, the potential TGDE reach of Wilkie Creek follows the contact between elevated regolith of Jurassic bedrock (and associated colluvial cover sediments) to the west which emerges from lower elevation alluvium of the Wilkie Creek and broader Condamine River Alluvium to the east. The current position of Wilkie Creek is relatively hard-up against the toe of the eastward slope off the bedrock regolith, and therefore follows the bedrock/alluvium geological contact in a south-to-north orientation.

A shallow anticline underlies the north-western elevated portion of the mapped TGDE, with the roughly 25m rise in the topography a subdued expression of the underlying subsurface structure. Here, Wilkie Creek runs parallel on the eastern side of the anticline with is intersected by a series of fault-bounded graben block structures and sub-vertical thrust faults, some of which extend through the full Surat Basin sequence to surface. Vertical throws across a number of the faults is interpreted to be up to 40 metres.

North of the Dalby-Kogan Road, WCM groundwater pressures are likely to be >10 mbGL across most of the study area. However, anomalous elevated groundwater levels (above Wilkie Creek) appear to be present across the elevated plateau west of Wilkie Creek, upon which the Wilkie Creek Coal Mine is located. The presence of numerous sub-vertical faults and "keystone structures" are likely to result in complexities and disruptions to the regional groundwater hydraulic regime. Faults may both enhance vertical flow, resulting in cross-formational mixing of groundwater, and also provide barriers to lateral flow resulting in compartmentalisation of the groundwater flow system. Barriers to groundwater lateral flow and enhanced vertical flow in some hydrogeological settings may result in anomalous pressure gradients and vertical discharges of mixed groundwater to surface (springs or stream baseflow).

Supporting the hypothesis for the presence of a mixing zone is groundwater quality and hydrogeochemistry analyses which show distinctive similarities between surface water and WCM and CRA groundwaters north of Dalby-Kogan Road. Supporting the hypothesis of a groundwater discharge zone into Wilkie Creek and/or the Wilkie Creek alluvium is the presence of ²²²radon in Wilkie Creek surface water.

Also of possible relevance is that the CRA sequence within the study area is relatively thin (shallow depth to bedrock) and is dominated by finer-grained (silt/clay-rich) sediments. This may result in lower recharge infiltration volumes and therefore limited dilution of laterally-discharging saline groundwater from the WCM. This is evident through review of lithological descriptions within bore logs and the lack of high flow rate irrigation bores present within the study area. Relatively low CRA permeabilities and limited extraction may also result in higher CRA and laterally-adjacent WCM pressures.

Given that there is evidence within the DRDMW groundwater database of the presence of both saline groundwater and elevated groundwater pressures in the area prior to the mine operation, it is considered most likely that these anomalies are due primarily to natural structural complexities in the geological setting.

However the onset of vegetation dieback around 1990 coinciding with other activities in the area and drought suggests the possibility of non-CSG stressors causing critical changes in hydrogeological conditions, likely related to shallow groundwater salinity levels.

Conclusions

Prior to commencement of significant identified hydrological and hydrogeological alteration which commenced in 1990, it is considered likely that vegetation within portions of the identified reach of Wilkie Creek and an extension downstream to the north was dependent, at least seasonally, on groundwater. This is consistent with the classification of river red gum as a facultative phreatophyte.

However severe degradation of the ecosystem including widespread mature tree dieback, likely due to exposure to shallow saline groundwater, has resulted in ecosystem collapse. In the current

hydrologeological regime, no trees within the affected reach were identified as being groundwater reliant. Elevated groundwater salinity is considered the major factor contributing to the poor ecological health of the reach of Wilkie Creek that is subject to this assessment. The riparian vegetation is still relatively intact immediately north of Dalby-Kogan Road where the preferential source of water appeared to be shallow soil moisture at the time of assessment.

The conceptual model identifies numerous potential stressors to the riparian ecosystem on Wilkie Creek which appear to have commenced from 1990 and are likely a result of activities otherthan Arrow's operations. Such hypotheses require further testing through additional work to address critical research gaps and subsequent refinement of the eco-hydrogeological conceptual model.

References

Doody, T., Colloff, M., Davies, M., Koul, V., Benyon, R., & Nagler, P. (2015). Quantifying water requirements of riparian river red gum (Eucalyptus camaldulensis) in the Murray–Darling Basin, Australia – implications for the management of environmental flows. Ecohydrology, 8(8), 1471-1487.

Doody, T. M., Holland K. L., Benyon R. G., and Jolly I. D. (2009). Effect of groundwater freshening on riparian vegetation water balance. Hydrological Processes 23.24: 3485-3499.

Holland K, Tyreman S, Mensforth L, Walker G. 2006. Tree water sources over shallow, saline groundwater in the lower River Murray, south eastern Australia: implications for groundwater recharge mechanisms. Australian Journal of Botany 54: 193–205.

Mensforth, L., Thorburn, P., Tyerman, S., & Walker, G. (1994). Sources of water used by riparian Eucalyptus camaldulensis overlying highly saline groundwater. Oecologia, 100(1), 21-28.

Thorburn, P. J, and Walker G. R (1994) Variations in stream water uptake by Eucalyptus camaldulensis with differing access to stream water. Oecologia, 100, 293-301.

Appendix E – Ground Movement Investigation Summary






Figure B-1: 1x1km Grid Cells (34 off) subject to investigation level assessment



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 161 of 168




Figure B-2: Transect locations taken within grid cells (156 off) as part of investigation level assessment



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 162 of 168

Table B-1: Change in average slope 2022 to 2023 along transects (13 June to 17 Aug 2022LiDAR Capture and 30 May to 26 Jun 2023 LiDAR Capture)

Profile (Line number, Grid		% Slope Change (2022 to	0.1% Slope Change
ID and DEM year)	% Slope (Least Squares)	2023)	Threshold Exceeded?
1_Grid1941_2022_DEM	0.060%		
1_Grid1941_2023_DEM	0.086%	0.026%	
2_Grid1941_2022_DEM	0.071%		
2_Grid1941_2023_DEM	0.106%	0.035%	
3_Grid1941_2022_DEM	0.043%		
3_Grid1941_2023_DEM	0.025%	-0.018%	
4_Grid1941_2022_DEM	0.116%		
4_Grid1941_2023_DEM	0.131%	0.015%	
1 Grid2039 2022 DEM	-0.082%		
1 Grid2039 2023 DEM	-0.070%	0.012%	
2 Grid2039 2022 DEM	-0.181%		
2 Grid2039 2023 DEM	-0.187%	-0.006%	
3 Grid2039 2022 DEM	-0.077%		
3 Grid2039 2023 DEM	0.039%	0.116%	YES
4 Grid2039 2022 DEM	-0.046%		
4 Grid2039 2023 DEM	-0.030%	0.016%	
5 Grid2039 2022 DEM	-0.139%		
5 Grid2039 2023 DEM	-0.147%	-0.008%	
6 Grid2039 2022 DEM	-0.349%		
6 Grid2039 2023 DEM	-0.344%	0.006%	
1 Grid2231 2022 DEM	0.169%		
1 Grid2231 2023 DEM	0.180%	0.011%	
2 Grid2231 2022 DEM	0.059%		
2 Grid2231 2023 DEM	0.102%	0.043%	
3 Grid2231 2022 DEM	0.069%	0.010/0	
3 Grid2231 2023 DEM	0.142%	0.073%	
4 Grid2231 2022 DEM	-0.067%	0.07070	
4 Grid2231 2023 DEM	-0.064%	0.003%	
5 Grid2231 2022 DEM	-0.005%		
5 Grid2231 2023 DEM	-0.012%	-0.007%	
6 Grid2231 2022 DEM	-0.302%		
6 Grid2231 2023 DEM	-0.312%	-0.009%	
1 Grid2308 2022 DEM	-0.069%		
1_Grid2308_2023_DEM	-0.060%	0.009%	
2 Grid2308 2022 DEM	-0.299%		
2 Grid2308 2023 DEM	-0.301%	-0.002%	
3 Grid2308 2022 DEM	0.098%		
3 Grid2308 2023 DEM	0.084%	-0.014%	
4 Grid2308 2022 DEM	0.243%		
4 Grid2308 2023 DEM	0.243%	0.000%	
1 Grid2346 2022 DEM	0.142%		
1 Grid2346 2023 DEM	0.138%	-0.004%	
2_Grid2346_2022_DEM	0.035%		
2 Grid2346 2023 DEM	0.030%	-0.005%	
3 Grid2346 2022 DEM	0.356%		
3 Grid2346 2023 DEM	0.373%	0.018%	
4 Grid2346 2022 DEM	0.336%		
4 Grid2346 2023 DEM	0.335%	0.000%	
5 Grid2346 2022 DEM	0.023%		
5 Grid2346 2023 DEM	0.351%	0.328%	YES
6 Grid2346 2022 DEM	0.182%		
6 Grid2346 2023 DEM	0.189%	0.007%	
7 Grid2346 2022 DEM	0.235%		
	0.20070		



S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 163 of 168

Profile (Line number, Grid	0/ Clane (Leest Courses)	% Slope Change (2022 to	0.1% Slope Change
ID and DEM year)	% Slope (Least Squares)	2023)	Threshold Exceeded?
7_Grid2346_2023_DEM	0.252%	0.017%	
8_Grid2346_2022_DEM	-0.092%		
8_Grid2346_2023_DEM	-0.090%	0.002%	
1_Grid2369_2022_DEM	-0.077%		
1_Grid2369_2023_DEM	-0.090%	-0.014%	
2 Grid2369 2022 DEM	-0.207%		
2 Grid2369 2023 DEM	-0.212%	-0.006%	
3 Grid2369 2022 DEM	-0.279%		
3 Grid2369 2023 DEM	-0.284%	-0.006%	
4 Grid2369 2022 DEM	0.036%		
4 Grid2369 2023 DEM	0.032%	-0.004%	
1 Grid2370 2022 DEM	0.118%		
1 Grid2370 2023 DEM	0.123%	0.005%	
2 Grid2370 2022 DEM	-0.032%		
2_Grid2370_2023_DEM	-0.026%	0.005%	
3 Grid2370 2022 DEM	0.041%		
3_Grid2370_2023_DEM	0.040%	-0.001%	
4 Grid2370 2022 DEM	0.071%		
4 Grid2370 2023 DEM	0.076%	0.005%	
5 Grid2370 2022 DEM	0.274%		
5 Grid2370 2023 DEM	0.261%	-0.013%	
	0.094%		
1 Grid2371 2023 DEM	0.080%	-0.014%	
2 Grid2371 2022 DEM	0.039%		
2 Grid2371 2023 DEM	-0.021%	-0.061%	
3 Grid2371 2022 DEM	-0.016%		
3 Grid2371 2023 DEM	-0.017%	-0.001%	
1 Grid2372 2022 DEM	0.051%		
1 Grid2372 2023 DEM	0.043%	-0.008%	
2_Grid2372_2022_DEM	0.204%		
2 Grid2372 2023 DEM	0.206%	0.002%	
3_Grid2372_2022_DEM	-0.076%		
3_Grid2372_2023_DEM	-0.074%	0.002%	
4 Grid2372 2022 DEM	-0.353%		
4 Grid2372 2023 DEM	-0.376%	-0.023%	
5_Grid2372_2022_DEM	-0.376%		
5_Grid2372_2023_DEM	-0.383%	-0.007%	
	-0.127%		
	-0.132%	-0.005%	
	-0.327%		
	-0.328%	-0.001%	
2_Grid2395_2022_DEM	-0.176%		
	-0.180%	-0.005%	
3_Grid2395_2022_DEM	-0.300%		
	-0.278%	0.023%	
	-0.149%		
4_Grid2395_2023_DEM	-0.161%	-0.012%	
5_Grid2395_2022_DEM	-0.060%		
	-0.043%	0.017%	
	-0.156%		
	-0.141%	0.015%	
	-0.054%		
	-0.074%	-0.020%	
	-0.439%		
	-0.450%	-0.012%	
	-0.516%		
	-0.520%	-0.004%	

S00-ARW-ENV-REP-00067 Released on 20/01/24 – Version 1.0 Page 164 of 168



Profile (Line number, Grid		% Slope Change (2022 to	0.1% Slope Change
ID and DEM year)	% Slope (Least Squares)	% Slope Change (2022 to 2023)	Threshold Exceeded?
4_Grid2396_2022_DEM	-0.288%	2023)	
4 Grid2396 2023 DEM	-0.297%	-0.009%	
5 Grid2396 2022 DEM	-0.122%	0.00070	
5 Grid2396 2023 DEM	-0.123%	-0.001%	
6 Grid2396 2022 DEM	-0.080%	0.001/0	
6 Grid2396 2023 DEM	-0.074%	0.006%	
7 Grid2396 2022 DEM	-0.107%		
7 Grid2396 2023 DEM	-0.103%	0.004%	
1 Grid2419 2022 DEM	-0.091%		
1 Grid2419 2023 DEM	-0.083%	0.008%	
2 Grid2419 2022 DEM	0.010%		
2 Grid2419 2023 DEM	-0.003%	-0.013%	
3 Grid2419 2022 DEM	-0.141%		
3 Grid2419 2023 DEM	-0.132%	0.009%	
4 Grid2419 2022 DEM	-0.216%		
4 Grid2419 2023 DEM	-0.229%	-0.013%	
5 Grid2419 2022 DEM	-0.299%		
5 Grid2419 2023 DEM	-0.307%	-0.008%	
6 Grid2419 2022 DEM	-0.175%		
6 Grid2419 2023 DEM	-0.173%	0.002%	
1 Grid2420 2022 DEM	-0.786%		
1 Grid2420 2023 DEM	-0.776%	0.011%	
2 Grid2420 2022 DEM	-0.211%		
2_Grid2420_2023_DEM	-0.214%	-0.003%	
3 Grid2420 2022 DEM	-0.226%		
3 Grid2420 2023 DEM	-0.224%	0.001%	
4 Grid2420 2022 DEM	-0.323%		
4 Grid2420 2023 DEM	-0.318%	0.005%	
5 Grid2420 2022 DEM	-0.426%		
5 Grid2420 2023 DEM	-0.446%	-0.020%	
1 Grid2421 2022 DEM	-0.276%		
1 Grid2421 2023 DEM	-0.278%	-0.002%	
2 Grid2421 2022 DEM	-0.219%		
2 Grid2421 2023 DEM	-0.211%	0.009%	
3 Grid2421 2022 DEM	-0.218%		
3 Grid2421 2023 DEM	-0.201%	0.016%	
4_Grid2421_2022_DEM	-0.225%		
4 Grid2421 2023 DEM	-0.216%	0.009%	
5 Grid2421 2022 DEM	-0.272%		
5 Grid2421 2023 DEM	-0.246%	0.027%	
6 Grid2421 2022 DEM	-0.305%		
6 Grid2421 2023 DEM	-0.293%	0.012%	
1 Grid2450 2022 DEM	-0.152%		
1 Grid2450 2023 DEM	-0.158%	-0.006%	
2 Grid2450 2022 DEM	0.143%		
2 Grid2450 2023 DEM	0.138%	-0.004%	
3 Grid2450 2022 DEM	0.108%		
3 Grid2450 2023 DEM	0.119%	0.012%	
4 Grid2450 2022 DEM	-0.278%		
4 Grid2450 2023 DEM	-0.288%	-0.009%	
1 Grid2571 2022 DEM	-0.110%		
1 Grid2571 2023 DEM	-0.221%	-0.111%	YES
2 Grid2571 2022 DEM	-0.003%		
2 Grid2571 2023 DEM	0.000%	0.003%	
3 Grid2571 2022 DEM	-0.116%		
3 Grid2571 2023 DEM	-0.124%	-0.009%	
4 Grid2571 2022 DEM	-0.017%		
	0.01775		




Profile (Line number, Grid	% Slope (Least Squares)	% Slope Change (2022 to	0.1% Slope Change
ID and DEM year)	% Slope (Least Squares)	2023)	Threshold Exceeded?
4_Grid2571_2023_DEM	-0.023%	-0.006%	
5_Grid2571_2022_DEM	-0.088%		
5_Grid2571_2023_DEM	-0.080%	0.008%	
1_Grid2603_2022_DEM	-0.196%		
1_Grid2603_2023_DEM	-0.191%	0.004%	
2 Grid2603 2022 DEM	-0.731%		
2 Grid2603 2023 DEM	-0.739%	-0.008%	
3 Grid2603 2022 DEM	-0.165%		
3 Grid2603 2023 DEM	-0.159%	0.006%	
4 Grid2603 2022 DEM	-0.201%		
4 Grid2603 2023 DEM	-0.199%	0.002%	
1 Grid2617 2022 DEM	-0.141%		
1 Grid2617 2023 DEM	-0.140%	0.000%	
2 Grid2617 2022 DEM	-0.404%		
2 Grid2617 2023 DEM	-0.401%	0.003%	
3 Grid2617 2022 DEM	-0.497%		
3 Grid2617 2023 DEM	-0.496%	0.001%	
4 Grid2617 2022 DEM	-0.052%		
4 Grid2617 2023 DEM	-0.051%	0.001%	
1 Grid2618 2022 DEM	-0.075%		
1 Grid2618 2023 DEM	-0.078%	-0.003%	
2 Grid2618 2022 DEM	-0.334%		
2 Grid2618 2023 DEM	-0.334%	0.000%	
3 Grid2618 2022 DEM	-0.571%	0.00070	
3 Grid2618 2023 DEM	-0.573%	-0.002%	
4 Grid2618 2022 DEM	-0.339%	-0.00276	
4 Grid2618 2023 DEM	-0.339%	0.001%	
1 Grid2641 2022 DEM	-0.433%	0.001%	
1 Grid2641 2023 DEM	-0.431%	0.002%	
2 Grid2641 2022 DEM	-1.457%	0.00276	
2 Grid2641 2023 DEM	-1.460%	-0.003%	
3 Grid2641 2022 DEM	-1.400%	-0.003%	
		0.001%	
3_Grid2641_2023_DEM	-1.173%	0.001%	
1_Grid2716_2022_DEM	-0.205%	0.004%	
1_Grid2716_2023_DEM	-0.210%	-0.004%	
2_Grid2716_2022_DEM	0.476%	0.005%	
2_Grid2716_2023_DEM	0.471%	-0.005%	
3_Grid2716_2022_DEM	0.526%	0.012%	
3_Grid2716_2023_DEM	0.513%	-0.013%	
4_Grid2716_2022_DEM	-0.584%	0.0129/	
4_Grid2716_2023_DEM	-0.602%	-0.018%	
5_Grid2716_2022_DEM	-0.226%	0.0000%	
5_Grid2716_2023_DEM	-0.220%	0.006%	
1_Grid2738_2022_DEM	-0.678%	0.0010/	
1_Grid2738_2023_DEM	-0.678%	-0.001%	
2_Grid2738_2022_DEM	-0.210%	0.005%	
2_Grid2738_2023_DEM	-0.205%	0.005%	
3_Grid2738_2022_DEM	-0.346%	0.0000/	
3_Grid2738_2023_DEM	-0.343%	0.003%	
4_Grid2738_2022_DEM	-0.328%		
4_Grid2738_2023_DEM	-0.320%	0.008%	
1_Grid2739_2022_DEM	-0.001%		
1_Grid2739_2023_DEM	0.010%	0.011%	
2_Grid2739_2022_DEM	-0.780%		
2_Grid2739_2023_DEM	-0.786%	-0.006%	
3_Grid2739_2022_DEM	-0.123%		
3_Grid2739_2023_DEM	-0.118%	0.005%	





Dusfile (line number Cuid		9/ Classe Charges (2022 to	
Profile (Line number, Grid ID and DEM year)	% Slope (Least Squares)	% Slope Change (2022 to 2023)	0.1% Slope Change Threshold Exceeded?
4 Grid2739 2022 DEM	-0.860%	2023)	Inreshold Exceeded?
4 Grid2739_2022_DEM 4 Grid2739 2023 DEM	-0.851%	0.009%	
1 Grid2740 2022 DEM	-0.092%	0:009%	
1 Grid2740_2022_DEM	-0.080%	0.012%	
2 Grid2740_2023_DEM	-0.063%	0.01276	
2_Grid2740_2022_DEM	-0.059%	0.004%	
3 Grid2740_2023_DEM	-0.059%	0.004%	
3 Grid2740_2022_DEM	-0.054%	0.005%	
4 Grid2740 2022 DEM	-0.038%	0.00370	
4 Grid2740_2022_DEM	-0.036%	0.002%	
1 Grid2759 2022 DEM	-0.260%	0.002/0	
1 Grid2759 2023 DEM	-0.256%	0.004%	
2 Grid2759 2022 DEM	0.145%	0.00470	
2 Grid2759 2023 DEM	0.144%	-0.001%	
3 Grid2759 2022 DEM	0.183%	0.001/0	
3 Grid2759 2023 DEM	0.205%	0.022%	
4 Grid2759 2022 DEM	-0.629%		
4 Grid2759 2023 DEM	-0.606%	0.024%	
5 Grid2759 2022 DEM	0.167%		
5 Grid2759 2023 DEM	0.154%	-0.014%	
6 Grid2759 2022 DEM	0.000%		
6 Grid2759 2023 DEM	-0.007%	-0.006%	
7 Grid2759 2022 DEM	-0.424%		
7_Grid2759_2023_DEM	-0.425%	-0.002%	
1 Grid2760 2022 DEM	-1.422%		
1 Grid2760 2023 DEM	-1.503%	-0.081%	
2 Grid2760 2022 DEM	0.325%		
2 Grid2760 2023 DEM	0.324%	-0.001%	
	-0.103%		
3 Grid2760 2023 DEM	-0.074%	0.029%	
1 Grid2761 2022 DEM	-0.171%		
1_Grid2761_2023_DEM	-0.161%	0.011%	
2_Grid2761_2022_DEM	-0.257%		
2_Grid2761_2023_DEM	-0.252%	0.005%	
1_Grid2787_2022_DEM	0.000%		
1_Grid2787_2023_DEM	-0.011%	-0.011%	
2_Grid2787_2022_DEM	0.043%		
	0.058%	0.016%	
	-0.198%		
	-0.194%	0.004%	
4_Grid2787_2022_DEM	-0.046%		
4_Grid2787_2023_DEM	-0.049%	-0.003%	
5_Grid2787_2022_DEM	-0.083%		
5_Grid2787_2023_DEM	-0.084%	-0.001%	
1_Grid2808_2022_DEM	-0.029%		
1_Grid2808_2023_DEM	-0.028%	0.001%	
2_Grid2808_2022_DEM	-0.085%		
2_Grid2808_2023_DEM	-0.090%	-0.004%	
3_Grid2808_2022_DEM	0.338%		
3_Grid2808_2023_DEM	0.331%	-0.007%	
1_Grid2833_2022_DEM	0.300%		
1_Grid2833_2023_DEM	0.300%	0.001%	
2_Grid2833_2022_DEM	3.542%		
2_Grid2833_2023_DEM	3.533%	-0.009%	
1_Grid3054_2022_DEM	-0.610%		
1_Grid3054_2023_DEM	-0.615%	-0.005%	
2_Grid3054_2022_DEM	-0.352%		





Profile (Line number, Grid ID and DEM year)	% Slope (Least Squares)	% Slope Change (2022 to 2023)	0.1% Slope Change Threshold Exceeded?
2_Grid3054_2023_DEM	-0.357%	-0.006%	
3_Grid3054_2022_DEM	-0.930%		
3_Grid3054_2023_DEM	-0.935%	-0.005%	
4_Grid3054_2022_DEM	-0.690%		
4_Grid3054_2023_DEM	-0.691%	-0.001%	
1_Grid2138_2022_DEM	-0.075%		
1_Grid2138_2023_DEM	-0.070%	0.005%	
1_Grid2720_2022_DEM	0.175%		
1_Grid2720_2023_DEM	0.162%	-0.014%	
1_Grid2767_2022_DEM	-0.277%		
1_Grid2767_2023_DEM	-0.284%	-0.007%	
2_Grid2138_2022_DEM	-0.126%		
2_Grid2138_2023_DEM	-0.116%	0.010%	
2_Grid2720_2022_DEM	-0.176%		
2_Grid2720_2023_DEM	-0.180%	-0.004%	
2_Grid2767_2022_DEM	0.228%		
2_Grid2767_2023_DEM	0.234%	0.006%	
3_Grid2138_2022_DEM	-0.032%		
3_Grid2138_2023_DEM	-0.018%	0.013%	
3_Grid2720_2022_DEM	-0.072%		
3_Grid2720_2023_DEM	-0.070%	0.002%	
3_Grid2767_2022_DEM	-0.016%		
3_Grid2767_2023_DEM	-0.055%	-0.039%	
4_Grid2138_2022_DEM	-0.110%		
4_Grid2138_2023_DEM	-0.106%	0.004%	
4_Grid2767_2022_DEM	-0.157%		
4_Grid2767_2023_DEM	-0.164%	-0.007%	
5_Grid2767_2022_DEM	-0.025%		
5_Grid2767_2023_DEM	-0.032%	-0.007%	
6_Grid2767_2022_DEM	-0.364%		
6_Grid2767_2023_DEM	-0.370%	-0.006%	